

RUPEDL U-NELI 5W-40 SN

● Description

RUPEDL U-NELI 5W-40 SN is a high-performance low friction oil, which is designed for gasoline and diesel engines of passenger cars, and which especially can be used for fuel injected and turbo charged engines.

It is blended from high quality hydrocracked base oils and selected additives. This makes for a lubricant quality which fulfills and exceeds all requirements of modern passenger car engines.

● Properties

RUPEDL U-NELI 5W-40 SN has following advantages to be pointed out:

- Excellent cold start and fast oil feed even at temperatures down to lower than -30°C assure fuel- and oil-economy.
- Optimized high temperature viscosity to meet latest requirements leads to low oil-caused emissions.
- High wear and corrosion protection and a very good dispersancy provide for an excellent cleanliness of the engine and for long motor life.
- All seasons use by outstanding temperature-viscosity properties and reliable performance reserves even at long drain intervals.

● Specifications/Recommendations

API SN / CF

ACEA A3 / B4

MB-Approval 229.5

BMW LongLife-01

Porsche A40

VW 502 00/505 00

Opel GM-LL-B-025

PSA B71 2296

Renault RN 0710 / 0700

Lamborghini

Maserati

● Typical Properties

Rupedl U-NELI 5W-40	Method	Unit	Value
Density at 15°C	DIN 51 757	kg/m ³	856
Viscosity at 100°C	DIN 51 562	mm ² /s	14,3
Viscosity Index	DIN ISO 2909		176
CCS at -30°C	DIN 51 377	mPa.s	6010
Pourpoint	DIN ISO 3016	°C	-36
Flashpoint	DIN ISO 2592	°C	224
TBN	DIN ISO 3771	mg KOH/g	10,4

*We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.