

## RUPEDL R-GAZELLE 10W-60

### ● Description and Properties

**RUPEDL R-GAZELLE 10W-60** is a fully synthetic fuel economy oil for all high-tech racing engines. It may be used in passenger cars gasoline and diesel engines, and here especially for modern performance-enhanced turbo charged and fuel injected engines. It is very well recommended for the use in motor-cycles with 4-stroke engines on the road as well as off-road.

**RUPEDL R-GAZELLE 10W-60** benefits from the combination of high-quality synthetic oils with specially optimized additives. Its expanded viscosity range gives additional security, even at continuous maximum load of the engine.

**RUPEDL R-GAZELLE 10W-60** provides excellent cold-starting properties. Due to the fast oil distribution the motor is effectively protected against cold-starting wear. Furthermore special additive components care for maximum wear protection under all service conditions. Optimal piston cleanliness and prevention of sludge built-up in the stagnant motor go without saying. The image of a high quality motor lubricant is completed by the fuel economy properties, which cause distinctly reduced fuel consumption.

### ● Specifications/Recommendations

ACEA A3 / B4

API SN / CF

## ● Typical Properties

<b>Rupedl R-GAZELLE 10W-60</b>	Method	Unit	Value
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	859
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	180
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	25,8
Viscosity Index	DIN ISO 2909		180
CCS at -25°C	DIN 51 377	mPa.s	5410
Pourpoint	DIN ISO 3016	°C	-42
Flashpoint	DIN ISO 2592	°C	226
TBN	DIN ISO 3771	mg KOH/g	13,6

\*We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.