



FISCHER TECHNICAL COMPANY

High Vacuum Pumps



Item: **LAV-7**

These 7 CFM (200 l/m) rotary style, 2 stage direct drive pumps are ideal for use in virtually all high vacuum applications. Our pumps are tested to 15 microns Hg but are suitable for all applications requiring a vacuum under 500 microns Hg. The pumps use High Vacuum Pump Oil (one quart included) and are designed to run on a closed and dry system. Regular oil changes and proper maintenance will ensure these pumps will last for years in your laboratory.



FISCHER TECHNICAL COMPANY

LAV-7 Specifications



High Vacuum Pump Specifications	
Free Air Displacement	200 l/m or 7 CFM
Factory Micron Rating	15 microns
Stages	2
Intake Fitting	1/2" Intake Hose Barb
Oil Capacity	23 oz (680cc)
Vacuum Pump Oil Refill	OIL-012 (12 Quarts) and OIL-PK (2 Quarts)
Motor Size	1/2 HP
Voltage	US 110V 60Hz
Approvals	UL Recognized
Shipping Weight	32 LBS
Shipping Dimensions	11" H x 14" L x 5 1/4" W (27.5cm x 35cm x 12.5cm)
Operating Temperature	30° F to 170° F
Pump Speed	1725 RPM
Manufactured In	USA