



Reinforcement Notes:

- BOTTOM:** 6x6 W2.9xW2.9 (6 gage) with 3/8" rods at 12" OC each way turned 12" into sidewalls
- TOP:** 6x6, W2.9xW2.9 (6 Gage) Welded Wire Fabric with 3/8" at 12" OC each way
- SIDEWALLS:** 6x6, W1.4xW1.4 (10 gage) Welded Wire Fabric with 3/8" rods at 20" OC horizontally.
- INTERIOR WALLS:** 6x6, W1.4xW1.4 (10 Gage) Welded Wire Fabric

ALL DIMENSIONS IN INCHES

ECOLOGICAL TANKS, INC
 2247 HWY 151 NORTH
 DOWNSVILLE, LA 71234
 318-644-0397 OFFICE
 318-644-7257 FAX

Model AA750-4290

NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN ANY RETRIEVAL SYSTEM, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF ECOLOGICAL TANKS, INC.

Treatment Capacity: 750 GPD	BOD Loading: 1.75 #/Day
SCALE: NTS	DATE: 1/9/19
REV: 0	ENG: TJR
DRAWING NO. AA750-4290.DWG	