


Group in Catalogue : **INTERIOR**

Ultra low glare COB Downlight



TECHNICAL DATA	Mounting: in the ceiling, with mounting brackets (included) Body: aluminum Colour: white RAL: 9003 Bezel colour / Detail: White/black/silver
ELECTRICAL DATA	Operating temperature range [°C]: -25 ... +40 Power: 220-240V 50/60Hz Includes light source: yes Electrical connection: max 3x1,5 mm ² wire
OPTICAL DATA	Light distribution: rotationally-symmetric Way of lighting: direct Reflector: Coated texture finish CRI/Ra: ≥90
GENERAL DATA	ULOR / DLOR: 0/100 GENERAL DATA Lifetime (L80B10): 60 000 h Warranty: 5 years Application: public utility facilities, delicatessen, supermarkets, shopping centers, offices, car showrooms, pathways, halls, classrooms, corridors



Code	Beam Angle	Power	Luminaire Lumens [Lm]	Efficacy [Lum/W]	CCT	CRI
SPK.DLS09	15	09	900	100	2700	90
SPK.DLS15	24	15	1500		3000	
SPK.DLS25	36	25	2500		3500	
SPK.DLS30	60	30	3000		4000	
					5000	

Luminous flux tolerance +/- 10%.
Power tolerance +/- 5%.
Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.
Up-to-date product info and General Warranty Terms available on our website www.spoke.net.au
Detailed information on luminous fluxes and powers for individual indexes are indicated on the product data sheet.
The parameters in the data sheet are given for Ta=25°C.
Colour temperature tolerance +/- 5%.

SPOKE Lighting reserves the right to introduce any construction changes and improvements into the lighting luminaires

Group in Catalogue : **INTERIOR**

Code	Dimensions (mm)	Hole Cut (mm)
SPK.DLS09	65(D) x 86(H)	55
SPK.DLS15	85 x 105	75
SPK.DLS25	105 x 132	95
SPK.DLS30	135 X 125	125



Luminous flux tolerance +/- 10%.
Power tolerance +/- 5%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.

Up-to-date product info and General Warranty Terms available on our website www.spoke.net.au

Detailed information on luminous fluxes and powers for individual indexes are indicated on the product data sheet.

The parameters in the data sheet are given for Ta=25°C.

Colour temperature tolerance +/- 5%.

SPOKE Lighting reserves the right to introduce any construction changes and improvements into the lighting luminaires