

demista

GENERAL SPECIFICATION

Approved to: EN60335-1:2002+A1,A2,A11,A12,A13,A14,A15 and EN60335-2-30:2009+A11

Power Rating: 200W/m²

Standard Voltage: 24V AC

Insulation Class: 2-double insulated

Thickness: 1 mm

IP Rating: 44

Cable connector: 30 x 40 x 5mm

Cable: 1m twin core 1.0mm² oval

Adhesive: acrylic

Material: Double insulated multi-layer polyester/polyethylene

Mirror temperature: Approximately 10 -15°C above ambient room temp.

Heating time: 3-5 minutes to start heating the mirror (depending on ambient room temperature)

Heat spread: Approximately 30% area around the pad

<i>demista</i> TM Model Number	Nominal Power (Watts)	Dimensions(mm)	Resistance range (Ohms)	Current (Amps)
7205	7	274 x 150	87.5-102.4	0.28
7210	15	274 x 265	65.3-76.2	0.37
7220	25	584 x 274	26.5-42.6	0.91
7225	36	462 x 424	15.2-17.5	1.57
7230	50	524 x 520	11.0-12.8	2.18
7233	44	800 x 300	12.5-14.6	1.8
7235	80	810 x 524	6.86-8.0	3.25
7240	100	1040 x 524	5.48-6.4	4.00
7250	150	1505 x 524	3.62-4.26	6.25

10 year warranty against any manufacturing fault, providing *demista*TM is fitted strictly in accordance with instructions supplied.

demista[®]

DEMISTA is a registered trademark of Demista Ltd

Telford Road, Glenrothes, Fife, KY7 4NX

Tel: +44 (0) 1932 866600

Email: sales@demista.co.uk

Fax +44 (0) 1932 866688

www.demista.co.uk