


Electric Scooter Moped



FALCON-1

Specifications

Dimension	2020 x 710 x 1160mm
Motor	2000W Brushless
Battery Type	72V27Ah/35Ah Lithium
Controller	Votol Intelligent controller
Intelligent Charger	72V3A
Charging Time	6hrs
Maximum Design Speed	58km/h
Range	85km/100km@30km/h
Wheelbase	1420mm
Ground Clearance	170mm
Loading Capacity	200KG
Climbing Angle	≤20°
Braking System	Fr. Disc/Re. Disc
Tire Size	130/60-13" Tubless
Net Weight	117KG
SKD Packing Dimension	1890 x 570 x 800mm
Loading Quantity SKD	75pcs per 40HQ



SUMMER /EEC

Specifications

Dimension	1860 x 710 x 1180mm
Motor	1500W Brushless
Battery Type	72V20AH Lead Acid / 72V20AH Lithium
Controller	Votol Intelligent controller
Intelligent Charger	72V3A
Charging Time	6hrs
Maximum Design Speed	25km/h or 45km/h
Range	55-100km
Wheelbase	1380mm
Ground Clearance	140mm
Loading Capacity	200KG
Climbing Angle	≤20°
Braking System	Fr. Disc/Re. Disc
Tire Size	90/80-12" Tubless
Net Weight	116KG
SKD Packing Dimension	1850 x 550 x 800mm
Loading Quantity SKD	75pcs per 40HQ



Rainbow



Specifications

Dimension	1780 x 740 x 1070mm
Motor	1000W Brushless
Battery Type	60V/72V20AH Lead Acid
Controller	12 Tube with 3 speed mode
Intelligent Charger	60V3A
Charging Time	6hrs
Maximum Design Speed	50km/h
Range	55-65km@30km/h
Wheelbase	1300mm
Ground Clearance	120mm
Loading Capacity	200KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Drum
Tire Size	3.0-10
Net Weight	100KG
SKD Packing Dimension	1750 x 460 x 750mm
Loading Quantity SKD	160sets / 96pcs per 40HQ



T15

Specifications

Dimension	1780 x 740 x 1070mm
Motor	1200W Brushless
Battery Type	72V20Ah/32Ah Lead Acid
Controller	12 Tube with 3 speed mode
Intelligent Charger	72V3A
Charging Time	6hrs
Maximum Design Speed	60km/h
Range	60-90km
Wheelbase	1330mm
Ground Clearance	120mm
Loading Capacity	200KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Drum
Tire Size	80/90-12" Tubless
Net Weight	108KG
SKD Packing Dimension	1700 x 570 x 800mm
Loading Quantity SKD	81pcs per 40HQ



E19S

Specifications

Dimension	1780 x 740 x 1070mm
Motor	1200W Brushless
Battery Type	72V20Ah/32Ah Lead Acid
Controller	12 Tube with 3 speed mode
Intelligent Charger	72V3A
Charging Time	6hrs
Maximum Design Speed	60km/h
Range	60-90km
Wheelbase	1330mm
Ground Clearance	120mm
Loading Capacity	200KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Disc
Tire Size	80/90-12" Tubless
Net Weight	108KG
SKD Packing Dimension	1700 x 570 x 800mm
Loading Quantity SKD	81pcs per 40HQ



BL-TESLA

Specifications

Dimension	1750 x 690 x 1270mm
Motor	1000W Brushless
Battery Type	60V/72V 20AH Lead Acid
Controller	60V/72V 30A 12Tube
Intelligent Charger	60V/72V 3A
Charging Time	6hrs
Maximum Design Speed	55km/h
Range	55-65km
Wheelbase	1300mm
Ground Clearance	135mm
Loading Capacity	200KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Drum
Tire Size	3.0-10
Net Weight	100KG
SKD Packing Dimension	1700 x 570 x 800mm
Loading Quantity SKD	81pcs per 40HQ



BL-MINI /EEC

Specifications

Dimension	1850 x 760 x 1150mm
Motor	1500W/3000W Brushless
Battery Type	60V30AH Lithium × 2
Controller	Votol Intelligent Controller
Intelligent Charger	60V5A
Charging Time	6hrs
Maximum Design Speed	60km/h or 80km/h
Range	120km@30km/h (60V30Ahx2)
Wheelbase	1340mm
Ground Clearance	175mm
Loading Capacity	200KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Disc
Tire Size	Fr. 90/90-12/ Re. 110/80-12" Tubless
Net Weight	110KG
SKD Packing Dimension	1750 x 570 x 830mm
Loading Quantity SKD	78pcs per 40HQ



Bentley

Specifications

Dimension	1470 x 660 x 1060mm
Motor	350W Brushless
Battery Type	48V12AH/20AH Lead Acid
Controller	6 Tube with pedal assist power USB charge plug
Intelligent Charger	48V1.8A/48V3A
Charging Time	6hrs
Maximum Design Speed	30km/h
Range	40-50KM
Wheelbase	1055mm
Ground Clearance	85mm
Loading Capacity	100KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	14-2.5
Net Weight	52KG
SKD Packing Dimension	1300 x 380 x 750mm
Loading Quantity SKD	214pcs per 40HQ



DING

Specifications

Dimension	1470 x 660 x 1060mm
Motor	350W Brushless
Battery Type	48V12AH/20AH Lead Acid
Controller	6 Tube with pedal assist power
Intelligent Charger	48V1.8A/48V3A
Charging Time	6hrs
Maximum Design Speed	30km/h
Range	40-50KM
Wheelbase	1055mm
Ground Clearance	85mm
Loading Capacity	100KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	14-2.5
Net Weight	52KG
SKD Packing Dimension	1300 x 380 x 750mm
Loading Quantity SKD	214pcs per 40HQ



MODERN

Specifications

Dimension	1470 x 660 x 1060mm
Motor	350W Brushless
Battery Type	48V12AH/20AH Lead Acid
Controller	9 Tube
Intelligent Charger	48V1.8A
Charging Time	6hrs
Maximum Design Speed	30km/h
Range	35km
Wheelbase	1055mm
Ground Clearance	130mm
Loading Capacity	100KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	3.00-8
Net Weight	52KG
SKD Packing Dimension	1470 x 320 x 660mm
Loading Quantity SKD	320pcs per 40HQ



STAR



Specifications

Dimension	1470 x 660 x 1060mm
Motor	350W Brushless
Battery Type	48V12AH Lead Acid
Controller	6 Tube
Intelligent Charger	48V1.8A
Charging Time	6hrs
Maximum Design Speed	30km/h
Range	35km
Wheelbase	1055mm
Ground Clearance	130mm
Loading Capacity	100KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	14-2.5
Net Weight	52KG
SKD Packing Dimension	1470 x 320 x 660mm
Loading Quantity SKD	320pcs per 40HQ



ROBIN S

Specifications

Dimension	1670 x 640 x 1020mm
Motor	450W Brushless
Battery Type	48V12AH/20AH Lead Acid/Lithium
Controller	9 Tube with 4 speed mode
Intelligent Charger	48V1.8A/48V3A
Charging Time	6-8h
Maximum Design Speed	35km/h
Range	35-50km
Wheelbase	1190mm
Ground Clearance	130mm
Loading Capacity	150KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	16-2.5
Net Weight	68KG
SKD Packing Dimension	1470 x 320 x 750mm
Loading Quantity SKD	191pcs per 40HQ



ROBIN D

Specifications

Dimension	1650 x 640 x 1050mm
Motor	450W Brushless
Battery Type	48V/60V 20AH Lead Acid
Controller	9 Tube with 4 speed mode
Intelligent Charger	48V/60V3A
Charging Time	6-8h
Maximum Design Speed	35km/h
Range	45-55km
Wheelbase	1200mm
Ground Clearance	130mm
Loading Capacity	150KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Drum
Tire Size	16-2.5
Net Weight	68KG
SKD Packing Dimension	1470 x 420 x 750mm
Loading Quantity SKD	147pcs per 40HQ



A9

Specifications

Dimension	1700×700×1080mm
Motor	1200W Brushless
Battery Type	48V20AH/60V50AH Lithium
Controller	60V32A
Intelligent Charger	48V3A/60V8A
Charging Time	6-8h
Maximum Design Speed	55km/h
Range	50km/110km
Wheelbase	1200mm
Ground Clearance	155mm
Loading Capacity	100KG
Climbing Angle	≤15°
Rim	Fr. Alum./Re.Alum.
Braking System	Fr. Disc/Re. Disc
Tire Size	80/90-12" Tubless
Net Weight	56KG
SKD Packing Dimension	1560×450×750
Loading Quantity SKD	111pcs per 40HQ

Electric Motorcycle



MAGIC

Specifications

Dimension	2050 x 740 x 1065mm
Motor	2500W Brushless
Battery Type	72V20Ah Lead Acid 60V30Ah*2 / 72V35Ah Lithium
Controller	Votol Intelligent controller
Intelligent Charger	72V3A
Charging Time	6 hours
Maximum Design Speed	58km/h
Range	55km/80km/110km
Wheelbase	1320mm
Ground Clearance	150mm
Loading Capacity	200KG
Climbing Angle	≤25°
Braking System	Fr. Disc/Re. Disc
Tire Size	Fr. 2.75-18 Re. 110/90-16
Net Weight	136KG
SKD Packing Dimension	93pcs per 40HQ
Loading Quantity SKD	2050 x 740 x 1065mm



CGW

Specifications

Dimension	1860×740×1060mm
Motor	1500W Brushless
Battery Type	72V20Ah Lead Acid 60V30Ah*2 / 72V35Ah Lithium
Controller	Votol Intelligent controller
Intelligent Charger	72V3A
Charging Time	6 hours
Maximum Design Speed	50km/h
Range	55km/80km/120km
Wheelbase	1310mm
Ground Clearance	150mm
Loading Capacity	200KG
Climbing Angle	≤25°
Braking System	Fr. Disc/Re. Disc
Tire Size	Fr. 2.75-18 Re. 3.0-17
Net Weight	105KG
SKD Packing Dimension	1690 x 460 x 800mm
Loading Quantity SKD	160sets/105pcs per 40HQ



BL-BOX

Specifications

Dimension	1980*800*1060 (mm)
Motor	4000W Brushless
Battery Type	60V30Ah*2 / 72V35Ah Lithium
Controller	Votol Intelligent controller
Intelligent Charger	72V5A
Charging Time	6 hours
Maximum Design Speed	80km/h
Range	100km@40km/h (60V30Ahx2)
Wheelbase	1310mm
Ground Clearance	175mm
Loading Capacity	150KG
Climbing Angle	≥20°
Braking System	Fr. Drum/Re.Drum
Tire Size	Fr. 3.0-17" Re.100/90-17"
Net Weight	105KG
SKD Packing Dimension	1750*460*800 (mm)
Loading Quantity SKD	96unit



PHOENIX

Specifications

Dimension	1800×650×1050mm
Motor	2000W Brushless
Battery Type	72V30A Lithium × 2
Controller	Votol Intelligent controller
Intelligent Charger	72V5A
Charging Time	6hrs
Maximum Design Speed	65-70km/h
Range	160km@30km/h(72V30Ah*2)
Wheelbase	1350mm
Ground Clearance	145mm
Loading Capacity	200KG
Climbing Angle	≤20°
Braking System	Fr. Disc/Re. Disc
Tire Size	Fr.90/90-14" Re.110/80-14" Tubless
Net Weight	110kg
SKD Packing Dimension	1940×570×1180mm
Loading Quantity SKD	84units per 40HQ



CPX /EEC

Specifications

Dimension	2120×710×1150mm
Motor	4000W Brushless
Battery Type	72V30A Lithium × 2
Controller	Votol Intelligent controller
Intelligent Charger	72V10AH
Charging Time	3hrs
Maximum Design Speed	90km/h
Range	140km@45km/h(72V30Ah*2)
Wheelbase	1430mm
Ground Clearance	160mm
Loading Capacity	120KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Disc
Tire Size	Fr.100/70-16" Re.110/80-14" Tubless
Net Weight	140KG
SKD Packing Dimension	1850 x 570 x 830mm
Loading Quantity CKD	68Unit(CKD)

Electric Tricycle



HARVEST



Specifications

Dimension	2960 x 1100 x 1350mm
Motor	1000W
Battery Type	60V45AH/58AH Lead Acid
Controller	18 tube 50A
Intelligent Charger	60V5A
Charging Time	8h
Maximum Design Speed	30km/h
Range	70-80km (unloaded)
Wheelbase	2500mm
Ground Clearance	200mm
Loading Capacity	500KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	Fr. 3.75-12 / Re.3.5-12
Net Weight	250KG
SKD Packing Dimension	2690 x 1070 x 750mm
Loading Quantity SKD	32pcs per 40HQ



LING

Specifications

Dimension	3070 x 1080 x 1720mm
Motor	48/60V 800W
Battery Type	60V45AH/58AH Lead Acid
Controller	18 tube 50A
Intelligent Charger	60V5A
Charging Time	8h
Maximum Design Speed	30km/h
Range	70-80km (unloaded)
Wheelbase	2500mm
Ground Clearance	200mm
Rear Axle Types	One-piece Gear Shift / Full Suspension
Loading Capacity	500KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	Fr. 350-12 / Re.375-12
Net Weight	250KG
SKD Packing Dimension	2690 x 1070 x 750mm
Loading Quantity SKD	32pcs per 40HQ



WIND8150



Specifications

Dimension	2950 x 1080 x 1340mm
Motor	48/60V 800W-1800W
Battery Type	60V45AH/58AH Lead Acid
Controller	18 Tube 50A
Intelligent Charger	60V5A
Charging Time	8h
Maximum Design Speed	30km/h
Range	70-80km (unloaded)
Wheelbase	2500mm
Ground Clearance	200mm
Rear Axle Types	One-piece Gear Shift / Full Suspension
Loading Capacity	500KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	Fr. 350-12 / Re.375-12
Net Weight	250KG
SKD Packing Dimension	2690 x 1070 x 750mm
Loading Quantity SKD	32pcs per 40HQ



WIND180

Specifications

Dimension	3330 x 1380 x 1430mm
Motor	60/72V 1500W-2000W
Battery Type	60V45AH/58AH Lead Acid
Controller	24 Tube
Intelligent Charger	60V5A
Charging Time	8h
Maximum Design Speed	30km/h
Range	70-80km (unloaded)
Wheelbase	2500mm
Ground Clearance	200mm
Rear Axle Types	One-piece Gear Shift / Full Suspension
Loading Capacity	500KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	Fr. 400-12 / Re.450-12
Net Weight	250KG
SKD Packing Dimension	2690 x 1070 x 750mm
Loading Quantity SKD	32pcs per 40HQ



TIGER180



Specifications

Dimension	3330 x 1380 x 1430mm
Motor	60/72V 1500W-2000W
Battery Type	60V45AH/58AH Lead Acid
Controller	24 Tube
Intelligent Charger	60V5A
Charging Time	8h
Maximum Design Speed	30km/h
Range	70-80km (unloaded)
Wheelbase	2500mm
Ground Clearance	200mm
Rear Axle Types	One-piece Gear Shift / Full Suspension
Loading Capacity	500KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	Fr. 400-12 / Re.450-12
Net Weight	250KG
SKD Packing Dimension	2690 x 1070 x 750mm
Loading Quantity SKD	32pcs per 40HQ



SILO

Specifications

Dimension	1800 x 690 x 1250mm
Motor	500W Brushless
Battery Type	60V20AH Lead Acid
Controller	12 tube with three speed mode
Intelligent Charger	60V3A
Charging Time	6hrs
Maximum Design Speed	32km/h
Range	60km
Wheelbase	1300mm
Ground Clearance	110mm
Loading Capacity	200KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Drum
Tire Size	3.0-10
Net Weight	116KG
SKD Packing Dimension	1420 x 720 x 800mm
Loading Quantity SKD	72pcs per 40HQ



Vacation-2

Specifications

Dimension	2800 x 1000 x 1780mm
Motor	1000W
Battery Type	60V120AH Lead-Acid
Controller	24 tube
Intelligent Charger	60V20A
Charging Time	6-8 hrs
Maximum Design Speed	40km/h
Range	100km
Wheelbase	2110mm
Ground Clearance	160mm
Loading Capacity	400KG
Climbing Angle	≤15°
Braking System	Fr. /Re. Drum
Tire Size	3.75-12
Net Weight	300KG
Loading Quantity SKD	40pcs per 40HQ
SKD Packing Dimension	2800 x 1000 x 1780mm



Vacation-3



Specifications

Dimension	2800 x 1250 x 1780mm
Motor	1800W
Battery Type	60V120AH Lead-Acid
Controller	30 tube
Intelligent Charger	60V20A
Charging Time	6-8 hrs
Maximum Design Speed	40km/h
Range	100km
Wheelbase	2220mm
Ground Clearance	170mm
Loading Capacity	500KG
Climbing Angle	≤15°
Braking System	Fr. Disc/Re. Drum
Tire Size	4.0-12
Net Weight	310KG
SKD Packing Dimension	40pcs per 40HQ



THANK YOU

