

Model 36BWT



36" BULL WHEEL TENSIONER

DIMENSIONS AND WEIGHTS

Length: 16' **Width:** 90" OAW
Height: 8' 11" **G.V.W.R.:** 18,250 lbs.
Empty Weight: 3800 lbs.
Payload: Approximately 14,450 lbs.

STANDARD FEATURES

Running Gear: Two 8,000 lb. single wheel axle with oil bath hubs
Brakes: 12 ¼" x 5" electric with self-charging break-away system
Landing Gear: 12,000 lb. static drop leg jack
Rear Jacks: Manual pin type
Wheels: 16" 8-hole Steel
Tires: 235/80R 16" 14-Ply
Frame: 6x4 rectangular tubing
Lights: Sealed beam with waterproof wiring in nylon tubing
Toolbox: 18"x18"x30"

UNIT PERFORMANCE

Continuous Rated Tension: 3,000 lbs
Line Speed: 0-4 mph

REEL CAPACITY

Maximum Reel Diameter: 72"
Maximum Reel Width: 55"
Maximum Reel Weight: 10,000 lbs
Shaft Diameter: 2-7/16"

Shaft Loading: Quick change reel shaft with accompanying hooks

Reel Brake: Manual hand crank caliper with 16" diameter bronze rotor

BULLWHEEL SYSTEM

Reel Diameter: 36" OD

Reel Width: 8"

Conductor Grooves: 4 at 1.25"

Bullwheel Brakes: Hydraulic actuated calipers from operator station with 24" diameter stainless steel rotors

Conductor Guide: 4 roller fairlead to insure proper alignment