




DISTRIBUTION EQUIPMENT

Model
PT15K

15K POLE TRAILER



SPECIFICATIONS

Length	Extendable length from 26.5' to 41.5' (7 pinpoints with 6 equal intervals @ 30" apart)
Width	82" OAW, with 81" Bolsters OAW (77.5" useable width)
Running Gear	One 15,000 lb. dual wheel axle with oil bath hubs
Brakes	12 ¼" x 5" electric with self-charging break-away system
Landing Gear	12,000 lb. static drop leg jack
Wheels	16" 8-hole Steel
Tires	235/80R 16" 14-Ply
Tongue	8" x 1/4" and 10 x 1/4" square tube; telescopes on rollers and UHMW
Frame	10" x 4" x 3/16" Rectangular Tubing & C 10 x 20 C-Channel
Coupling System	42,000 lb capacity x 2 ½" pintle eye, adjustable in 2 ¼" increments
Lights	Sealed beam with waterproof wiring in nylon tubing
G.V.W.R.	17,000 lbs.
Empty Weight	4200 lbs.
Payload	Approximately 12,800 lbs.
Misc.	Tie down straps, wheel chocks, safety chains, slide intube stanchions with keeper pins

OPTIONS

Additional length / Electric over hydraulic disc or drum brakes / Extended storage area
Custom paint color / Toolbox / Sliding Stanchions