



10 TON HYDRAULIC TAIL GOOSENECK TRAILERS

Standard Specifications:

- 20,000 lb. GVWR
- 12" x 19 lb. I-Beam Main Frame (w/ 4" anti-twist pipe)
- 12" Master-crafted Uni-Beam Gooseneck & Bulkhead
- 3" channel crossmembers - pierced frame - 16" OC
- 34" deck height x 102" overall deck width
- Dexter 10,000 lb. Oil Bath Spring Axles
- Electric brakes (12 1/2 " x 3 3/8 ")
- 235 80 r 16 E (8-lug) (10 ply radials)
- Adjustable Gooseneck Coupler (24K)
- Dual 12,000 lb. Hydraulic jacks
- Tool box w/ locking lid
- Stake pockets & rub rail
- Wireless dual function remote (120V plug-in battery charger)
- 2" Pressure Treated Pine Floor
- 10' Hydraulic Tail
- Lifetime LED lights w/ sealed wiring (7-way RV)
- 2K Automotive grade polyurethane paint (w/ primer)
- 3-Year Frame, 5 Year Axle, 1 Year Manufacturer Warranty

Popular Options

- Spare Tire & Mount
- 12,000 lb. axles (25,900 lb. GVWR)
- Tire Upgrades
- Optional Color
- Oak Floor
- Top Deck over Gooseneck
- Fork Holders
- 12,000 lb. winch
- Torsion Axles
- Electric over Hydraulic Brakes
- Hotshot/Accessories & Set-up

Models:

- 8530GN10T-HT (20' x 10')
- 8540GN10T-HT (30' x 10')



FULL CUSTOMIZATION AVAILABLE!

batrailer.com