



25 Ton Kingpin Drop-Deck Trailer

GVWR: 50,000 lbs. (70,000 lb. tri-axle option)

Main Frame: 14" I-Beam

Inside cross members: 6" channel

Top cross members: 4" channel (w/ frame braces)

Deck Height / Width: 35" x 102"

Sides: stake pockets & rub-rail or D-rings

Bulkhead: ¼" checker-plate

Jack: (2) Dual Ram 50K drop leg (dual-speed)

Axles: (2) 25,000 lb. oil bath (3 – 25,000 lb. axle 35 ton model)

Suspension: Hutch 9700 US

Brake: Air w/ ABS

Wheels: 17.5" dual, 8 lug

Tires: (8) – 215 75 R 17.5, 16 ply radials (18 ply option)

Boarding Step: Front driver side

Storage: tool tray in top deck w/ locking lid

Fenders: 1/4" checker plate over tires

Floor: 2" x 8" OAK

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided

Ramp Models

- 8.540KP25T (10' top + 24' flat + 6' tail)
- 8.545KP25T (10' top + 29' flat + 6' tail)

Flatbed Models

- 8.540KP25T (10' top + 30' flat)
- 8.553KP25T (10' top + 43' flat)



FEATURES & HIGHLIGHTS



RAMP MODEL



6' X 36" AIR ASSIST RAMPS



SLOPE DECK MODEL OPTION



TRI-AXLE 35 TON MODEL AVAILABLE

AIR ASSIST 11' BI-FOLD RAMP OPTION AVAILABLE

STEEL CHECKER-PLATE FLOOR OPTION AVAILABLE

FRONT LIFT AXLE OPTION (TRI -AXLE)