



3.5 Ton Low-Pro Tilt Trailer

Models: 512T3.5TT (12 L' x 60" W) - 612T3.5TT (12' L x 72" W) - 712T3.5TT (12' L x 80" W)

GVWR: 7,000 lbs. (estimated weight 1,800-2000 lbs)

Load Capacity: 5,000 lbs.

Main Frame: 5" x 3" x ¼ angle

Tongue: 4" I-Beam

Tilt bed cross members: 3" channel

Deck Height: 17 ½"

Jack: Ram 7K drop leg

Coupler: adjustable channel hitch w/ 2 5/16" ball

Axles: 7,000 lb. spring suspension EZ lube with electric brake

Wheels: 16" single, 8 lug

Tires: 235 80 R 16 E, 10 ply radials

Tie Downs: (4) ½" d-ring or stake pockets & rub-rail

Storage: tool tray w/ solid bottom in tongue

Floor: 1/8" steel checker-plate (optional bed liner coating, optional wood floor)

Hydraulics: 2" tie-rod self-dampening cylinder (w/ flow-control)

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided

