



5 Ton Low-Pro Equipment Trailer

Model: 718T5T

GVWR: 10,000 lbs. (estimated weight – 2,400 lbs.)

Load Capacity: 7,600 lbs.

Main Frame: 5" structural channel (C5 x 6.7)

Inside cross members: 3" channel (C3 x 4.1)

Deck height x width: 17" x 82" inside fenders

Flatbed: 18' wood

Ramps: 5' spring assist ramps (stand-up)

Tie Downs: stake pockets & rub-rail

Jack: Ram 7K drop leg

Coupler: adjustable hitch w/ 2 5/16" ball (21K Demco EZ-Latch)

Axles: (2) 6,000 lb. spring suspension, EZ lube with electric brake

Wheels: 15" single, 6 lug

Tires: (4) – 225 75 R 15, 10 ply radials

Storage: solid floor in tongue (w/ locking lid)

Fenders: 1/8" HD checker plate

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional colors available)

Warranty: 1 year with MSO provided

**** We can customize ****



