

10 Ton Low-Pro Equipment Trailer

Model: 720T10T (available in B&A Uni-Beam Gooseneck Model)

GVWR: 22,000 lbs. (estimated weight – 5,500 lbs.)

Load Capacity: 16,500 lbs.

Main Frame: 10" I-Beam (W10 x 19)

Inside cross members: 3" channel (C3 x 4.1)

Deck height x width: 26" x 82" inside fenders (drive-over full width option)

Flatbed: 18' wood + 2' tail (3' tail option w/ 3' B&A Jumbo Ramps)

Ramps: 5' spring assist (3' jumbo ramp option)

Sides: stake pockets and rub rail

Jack: Ram 12K drop leg (spring-loaded)

Coupler: 3" pintle eye (60K adjustable plate mount)

Axles: (2) 10,000 lb. Torsion suspension, EZ lube with electric brake

Wheels: 17.5" single, 8 lug

Tires: (4) – 235 75 R 17.5 single, 18 ply radials

Storage: full HD checker plate tool tray w/locking lid

Fenders: 3/16" HD checker plate **Floor:** 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closure

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black

Warranty: 1 year with MSO provided

