



10 Ton Tag-A-Long Low Profile Uni-Beam Tilt Bed Trailer

Model: 720T10TT (available in B&A Uni-Beam Gooseneck Model)

GVWR: 21,500 lbs. (estimated weight – 5,000 lbs.)

Load Capacity: 16,500 lbs.

Main Frame: 8" I-Beam (W8 x 15)

Inside frame cross members: 3" channel (16" on center)

Bed Main tilt frame: 6" channel

Tilt Bed: 16' wood

Front Stationary: 4' wood

Cylinder: gravity feed self-dampening cylinder w/ flow-speed control & lock-out

Width: 82" inside fenders (79 ½" wide tilt bed)

Sides: stake pockets and rub rail

Jack: Ram 12K drop leg

Coupler: adjustable plate mount, 2 5/16" Demco ez-latch

Axles: (2) 10,000 lb. Dexter Torsion suspension, oil bath with electric brake

Wheels: 17.5" single, 8 lug

Tires: (4) 235 75 R 17.5, 18 ply radials

Fenders: 1/8" checker plate HD

Floor: 2" x 8" Pressure treated pine

Storage: solid bottom floor in tongue (w/ locking HD tongue lid)

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced & loomed

Lights: LED (meets all DOT requirements)

Paint: cleaned, primed and painted 100% Black (optional colors)

Warranty: 1 year with MSO provided

