



7 Ton Low-Pro Equipment Trailer

Model: 720T7T (available in B&A Uni-Beam Gooseneck Model)

GVWR: 14,000 lbs. (estimated weight – 3,200 lbs.)

Load Capacity: 10,800 lbs.

Main Frame: 6" I-Beam (W6 x 9)

Cross members: 3" channel (C3 x 4.1)

Deck height x width: 20" x 82" inside fenders

Flatbed: 20' wood (available in 16' & 18' options)

Ramps: 5' spring assist (adjustable stiff knees)

Sides: stake pockets and rub rail (front driver side boarding step)

Jack: Ram 12K drop leg (spring loaded)

Coupler: adjustable hitch w/ 2 5/16" ball (21K Demco EZ-Latch)

Axles: (2) 7,000 lb. spring suspension, EZ lube with electric brake

Wheels: 16" single, 8 lug

Tires: (4) - 235 80 R 16 E, 10 ply radials

Storage: solid floor in tongue (w/ locking Jumbo deck lid, shock assisted)

Fenders: 1/8" checker plate

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional colors available)

Warranty: 1 year with MSO provided

**** We can customize ****



FEATURES & HIGHLIGHTS



20' FULL LENGTH FLAT W/ 82" INSIDE FENDERS



3" CHANNEL CROSSMEMBERS 16" OC I-BEAM MAIN FRAME



1/8" CHECKER-PLATE "B&A BUILT™" FENDERS



UNI-BEAM GOOSENECK MODEL OPTION



JUMBO LOCKING TOOL BOX



GAS SHOCK ASSIST