



### **7 Ton Tag-A-Long Low Profile Tilt Bed Trailer**

**Model:** 720T7TT (available in B&A Uni-Beam Gooseneck Model)

**GVWR:** 14,000 lbs. (estimated weight – 3,850 lbs.)

**Load Capacity:** 10,150 lbs.

**Main Frame, tilt bed & tongue:** 6" channel

**Inside frame cross members:** 3" channel (16" on center)

**Tilt Bed:** 16' wood (18' available)

**Front Stationary:** 4' wood (6' available)

**Cylinder:** 2" bore gravity feed self-dampening cylinder w/ reservoir & flow-speed control

**Tongue:** 5' (wrap under double frame stack)

**Width:** 82" deck & loading width (77" wide tilt bed)

**Sides:** stake pockets and rub rail

**Jack:** Ram 12K drop leg (spring loaded)

**Coupler:** adjustable hitch w/ 2 5/16" ball (21K Demco EZ-Latch)

**Axles:** (2) 7,000 lb. spring suspension, EZ lube with electric brake

**Wheels:** 16" single, 8 lug

**Tires:** 235 80 R 16 E, 10 ply radials

**Fenders:** 1/8" checker plate

**Floor:** 2" x 8" Pressure treated pine

**Storage:** solid bottom floor in tongue (w/ locking lid)

**Breakaway kit:** 12 Volt battery, with charge wire and LED test light

**Safety chains:** (2) 3/8" w/ hook and closures

**Wiring:** run in conduit tubing with junction boxes and neatly spliced

**Lights:** LED (meets all DOT requirements)

**Paint:** cleaned, primed and painted 100% Black (optional color)

**Warranty:** 1 year with MSO provided



**FEATURE & HIGHLIGHTS**



*HD DOUBLE STACK CHANNEL FRAME*



*EASY LOAD FULL WIDTH LOAD ANGLE  
HD "B&A BUILT™" FENDERS*



*HYDRAULIC GRAVITY FEED CUSHION  
CYLINDER W/ CONTROL SPEED*



*"B&A DUAL POINT LATCH  
LOCKING SYSTEM™"*



*LOCKING LID TOOL TRAY, 12K JACK  
SEALED WIRING, LED LIGHTS*



*PRESSURE TREATED PINE FLOOR*