



8 Ton Low-Pro Equipment Trailer

Model: 720T8T

GVWR: 16,000 lbs.

Main Frame: 8" structural channel (8" I-Beam gooseneck package)

Inside cross members: 3" channel (16" on center)

Deck height x width: 23" x 80" inside fenders

Flatbed: 20' wood (16' & 18' available)

Ramps: 5' spring assist

Sides: stake pockets and rub rail

Jack: Ram 12K drop leg

Coupler: adjustable hitch w/ 3" pintle eye

Axles: (2) 8,000 lb. 4" drop spring suspension, EZ lube with electric brake

Wheels: 17.5" single, 8 lug

Tires: (4) - 215 75 R 17.5, 16 ply radials

Spare Tire: mounted front bulkhead

Storage: mesh bottom floor in tongue (w/ locking lid)

Fenders: 1/8" checker plate

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided



FEATURE & HIGHLIGHTS



20' FULL LENGTH FLAT W/ 80"
INSIDE FENDERS



3" CHANNEL CROSSMEMBERS 16" OC
8" CHANNEL MAIN FRAME



17.5" WHEEL & 16 PLY TIRES STANDARD



23" DECK HEIGHT – 4" DROP AXLES



SPRING ASSIST RAMPS
ADJUSTABLE GROUND SUPPORTS



GOOSENECK PACKAGE OPTION