



8 Ton Low-Pro Equipment Trailer

Model: 720T8T (available in B&A Uni-Beam Gooseneck Model)

GVWR: 16,000 lbs. (estimated weight – 3,500 lbs.)

Load Capacity: 12,500 lbs.

Main Frame: 8" I-Beam (W8x10)

Inside cross members: 3" channel (C3 x 4.1)

Deck height x width: 22" x 80" inside fenders

Flatbed: 20' wood (available in 16' & 18' options)

Ramps: 5' spring assist (adjustable stiff knees)

Sides: stake pockets and rub rail (front driver side boarding step)

Jack: Ram 12K drop leg (spring loaded)

Coupler: adjustable hitch w/ 2 5/16" ball (21K Demco EZ-Latch)

Axles: (2) 8,000 lb. spring suspension, EZ lube with electric brake (12 1/4" x 3 3/8")

Wheels: 17.5" single, 8 lug

Tires: (4) - 215 75 R 17.5, 16 ply radials

Storage: solid bottom floor in tongue (w/ locking Jumbo deck lid, shock assisted)

Fenders: 1/8" checker plate

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided

**** We can customize ****



FEATURE & HIGHLIGHTS



HD CHECKER-PLATE TONGUE LID ALLOWS EXTRA DECK SPACE & AMPLE STORAGE



SPARE TIRE OPTION, PRESSURE TREATED PINE DECK, POCKETS & RUB-RAIL, BOARDING STEP



I-BEAM FRAME, HD CHECKERPLATE FENDERS, SPRING ASSIST RAMPS