

8 Ton Low-Pro Tilt Bed Trailer

Model: 720T8TT **GVWR:** 16,000 lbs.

Main Frame: 7" structural channel (8" I-Beam gooseneck package)

Inside frame cross members: 3" channel (16" on center)

Bed Main tilt frame: 7" channel **Tilt Bed:** 16' wood (18' available) **Front Stationary:** 4' wood

Cylinder: 2" bore gravity feed self-dampening cylinder w/ reservoir & flow-speed control

Tongue: 5' (wrap under double frame)

Width: 82" inside fenders, 80" deck (75" wide tilt bed)

Sides: stake pockets and rub rail

Jack: Ram 12K drop leg

Coupler: adjustable channel mount, 3" pintle eye

Axles: (2) 8,000 lb. spring suspension, EZ lube with electric brake

Wheels: 17.5" single, 8 lug

Tires: 215 75 R 17.5, 16 ply radials **Spare Tire:** mounted front bulkhead

Fenders: 1/8" checker plate

Floor: 2" x 8" Pressure treated pine

Storage: mesh bottom floor in tongue (w/ locking lid)

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED (meets all DOT requirements)

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided



FEATURE & HIGHLIGHTS



HD DOUBLE STACK CHANNEL FRAME



EASY LOAD FULL WIDTH LOAD ANGLE HD "B&A BUILT™" FENDERS



HYDRAULIC GRAVITY FEED CUSHION

CYLINDER W/ CONTROL SPEED



"B&A DUAL POINT LATCH LOCKING SYSTEM™"



LOCKING LID TOOL TRAY, 12K JACK SEALED WIRING, LED LIGHTS



GOOSENECK PACKAGE OPTION