



### **8 Ton Tag-A-Long Low Profile Uni-Beam Tilt Bed Trailer**

**Model:** 720T8TT

**GVWR:** 16,000 lbs. (estimated trailer weight – 4,500 lbs.)

**Load Capacity:** 11,500 lbs.

**Main Frame:** 12" I-Beam

**Inside frame cross members:** 3" channel (16" on center)

**Bed Main tilt frame:** 7" channel

**Tilt Bed:** 16' wood

**Front Stationary:** 4' wood

**Cylinder:** gravity feed self-dampening cylinder w/ flow-speed control & lock-out

**Width:** 82" inside fenders (75" wide tilt bed)

**Sides:** stake pockets and rub rail

**Jack:** Ram 12K drop leg (spring loaded)

**Coupler:** adjustable plate mount w/ 2 5/16" ball (21K Demco EZ-Latch)

**Axles:** (2) 8,000 lb. spring suspension, EZ lube with electric brake (12 1/4" x 3 3/8")

**Wheels:** 17.5" single, 8 lug

**Tires:** 215 75 R 17.5, 16 ply radials

**Fenders:** 1/8" checker plate HD

**Floor:** 2" x 8" Pressure treated pine

**Storage:** solid bottom floor in tongue (w/ locking HD jumbo tongue lid)

**Breakaway kit:** 12 Volt battery, with charge wire and LED test light

**Safety chains:** (2) 3/8" w/ hook and closures

**Wiring:** run in conduit tubing with junction boxes and neatly spliced & loomed

**Lights:** LED (meets all DOT requirements)

**Paint:** cleaned, primed and painted 100% Black (optional colors)

**Warranty:** 1 year with MSO provided



**FEATURES & HIGHLIGHTS**



***HD LOCKING TONGUE LID W/ GAS STRUT SHOCKS & DEEP WELL BOX PROVIDES AMPLE STORAGE & VALUABLE EXTRA DECK SPACE***



***HD ONE PIECE 12" BEAM FRAME DESIGN W/ BOARDING STEP AND HD CHECKERPLATE FENDERS***



***EASY LOAD ANGLE, 8K AXLES W/ 12 1/4" X 3 3/8" ELECTRIC BRAKE, 215 75 R 17.5 (16 PLY) RADIAL TIRES***