



10 Ton Gooseneck Deck-Over Dump Trailer

Model: 8.520GND10T

GVWR: 25,000 (estimated weight – 8,000 lbs.)

Load Capacity: 17,000 lbs.

Main Frame: 12" I-Beam (W12 x 16)

Gooseneck: B&A 12" Master-crafted Uni-Beam

Inside cross members: 5" x 3" x ¼" tube

Bed Main Frame & crossmembers: 7" channel & 3" channel (16" on center)

Deck Length / Height / Width: 20' x 34" x 96" (inside)

Cubic Yardage: 21.75 cu. Yds.

Floor: 3/16" smooth plate (7 ga.)

Sides: 44" height x 10 ga smooth plate (w/ tarp hooks)

Sides Standards: 3" x 1 ½" tube standards 24" on center

Rear Doors: (2) 44" barn doors w/ dual cam latch

Jack: (2) Dual Ram 12K drop leg (spring loaded)

Coupler: 2 5/16" adjustable pipe

Hoist: Power Hoist 630 scissor hoist rated @ 13 ton

Control: Push button w/ remote and plug-in cord

Power: electric/hydraulic pump w/ deep-cycle marine battery & plug-in charger

Axles: (2) 10,000 lb. spring suspension, oil bath with electric brake

Wheels: 16" dual, 8 lug

Tires: (8) - 235 80 R 16 E, 10 ply radials

Storage: locking tool tray b/t gooseneck uprights

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring & lights: sealed wiring w/ LED lights

Paint: cleaned, primed and painted 100% Black (optional colors)

Warranty: 1 year with MSO provided



FEATURES & HIGHLIGHTS



13 TON SCISSOR HOIST



REAR BARN DOORS



OPTIONAL TARP KIT



OPTIONAL SPREADER GATE



OPTIONAL RAMP PACKAGE



OPTIONAL HONDA™ PONY MOTOR