

8 Ton Deck-Over Equipment Trailer

Model: 8.524T8T **GVWR:** 16,000 lbs.

Main Frame: 10" I-Beam (W10 x 15) (10" I-Beam gooseneck package)

Inside cross members: 4" channel

Top cross members: 3" channel (16" on center)

Deck Height / Width: 34" x 102"

Flatbed: 20' wood Beavertail: 4' wood

Ramps: 5' spring assist, angle cleats (stand-up) **Sides:** 6" channel w/ stake pockets and rub rail

Jack: Ram 12K drop leg

Coupler: adjustable channel hitch w/ 3" pintle eye

Axles: (2) 8,000 lb. spring suspension, EZ lube with electric brake

Wheels: 17.5" single, 8 lug

Tires: (4) – 215 75 R 17.5, 16 ply radials **Spare Tire:** mounted front bulkhead **Boarding Step:** Front driver side

Storage: tool tray w/ mesh bottom in tongue & locking lid

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided



FEATURES & HIGHLIGHTS



TOOL TRAY W/ LOCKING LID, SPARE TIRE 12K JACK, BOARDING STEP



PRESSURE TREATED PINE FLOOR



10" I-BEAM W/ 16" CENTER CROSS-MEMBER FULL-LENGTH RUB RAIL & STAKE POCKETS



SPRING-ASSIST RAMPS
ADJUSTABLE GROUND SUPPORTS



FULLY SEALED WIRING & LED LIGHTS



GOOSENECK PACKAGE AVAILABLE