



12 Ton Gooseneck Deck-Over Low-Pro Equipment Trailer

Model: 8.525GN12T

GVWR: 25,900 lbs. (estimated weight – 6,400 lbs.)

Load Capacity: 19,500 lbs.

Main Frame: 12" I-Beam (W12 x 19)

Inside cross members: 6" channel

Cross members: 3" channel (pierced frame)

Deck Height / Width: 34" x 102"

Flatbed: 20' wood

Beavertail: 5' self-cleaning angle cleats

Ramps: 5' spring assist, angle cleats (stand-up)

Sides: 6" channel w/ stake pockets (24" on center) and rub rail

Gooseneck: 12" B&A Master-crafted Uni-Beam

Bulkhead: 1 ½" pipe front rack

Jack: (2) Dual Ram 12K drop leg (spring loaded)

Coupler: 2 5/16" adjustable pipe

Axles: (2) 12,000 lb. spring suspension, oil bath with electric brake

Wheels: 16" dual, 8 lug

Tires: (8) - 235 80 R 16 E, 10 ply radials

Boarding Step: Front driver side

Storage: steel tool tray b/t gooseneck uprights w/ locking lid

Fenders: 3/16" checker plate over tires

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional colors)

Warranty: 1 year with MSO provided



FEATURES & HIGHLIGHTS



**12" I-BEAM FRAME – 102" WIDE
34" DECK HEIGHT**



**DUAL JACKS - LOCKING
TOOL BOX – STEP – BULKHEAD**



**LOW-PRO PIERCED FRAME DESIGN
FULL-LENGTH RUB RAIL & STAKE POCKETS**



**TOP DECK OPTION
HYDRAULIC JACK OPTION**



10' HYDRAULIC TAIL OPTION



**FULL-WIDTH "B&A JUMBO RAMPS™" OPTION
SPRING ASSIST**