

20 Ton Tag-A-Long Deck-Over Equipment Tilt Trailer

Model: 8.525T20TT **GVWR:** 48,500 lbs.

Load Capacity: 40,000 lbs.

Main Frame: 14" I-Beam (W14 x 26)

Inside cross members: 6" channel (C6 x 8.2)

Top cross members: pierced frame 4" channel (C4 x 5.4) (16" OC)

Tilt Bed Frame: 8" x 4" x ¼" tube **Deck Height / Width:** 35 ¾" x 102"

Tongue: 5'

Front stationary Deck: 5'

Tilt Bed: 20'

Tilt Cylinders: (2) 2.5" bore cylinder (w/ flow control & gravity feed)

Side rail: 8" channel (C8 x 11.5)
Tie Downs: (5) HD 1" d-rings per side

Jack: (1) Ram 25K dual speed

Coupler: adjustable ¾" plate hitch w/ 3" pintle eye

Axles: (2) 25,000 lb. oil bath

Brakes: 12 1/4" x 7 1/2" Air w/ ABS (2S/1M system) park brake one axle

Suspension: Hutch 9700 US Wheels: 17.5" dual, 8 on 275 mm

Tires: (8) – 215 75 R 17.5 H, 16 ply radials

Boarding Step: Front driver side

Storage: tool tray w/solid bottom & steel locking lid in tongue

Fenders: 1/4" checker plate over tires

Floor: OAK

Safety chains: (2) 1/2" GD. 70 w/ hook and closures

Wiring: run in 1" conduit tubing with junction boxes (7-way tractor Pluq)

Lights: LED (separate rear stop & turn lights)

Paint: cleaned, primed and painted 100% black (optional color)

Warranty: 1 year with MSO provided

