



### **8 Ton Tag-A-Long Deck-Over Equipment Trailer**

**Model:** 8.525T8T

**GVWR:** 16,500 lbs. (estimated weight – 5,000 lbs.)

**Load Capacity:** 11,500 lbs.

**Main Frame:** 10" I-Beam (W10x15)

**Inside cross members:** 6" & 4" channel

**Top cross members:** 3" channel (16" on center)

**Deck Height / Width:** 34" x 102"

**Flatbed:** 20' wood

**Beavertail:** 5' self-cleaning angle cleats

**Ramps:** 5' x 44" wide "B&A JUMBO RAMPS™", spring assist, deck-level angle cleat

**Sides:** 6" channel w/ stake pockets and rub rail

**Jack:** (2) Dual Ram 12K drop leg (spring loaded)

**Coupler:** adjustable hitch w/ 2 5/16" ball (21K Demco EZ-Latch)

**Axles:** (2) 8,000 lb. spring suspension, EZ lube with electric brake (12 1/4" x 3 3/8")

**Wheels:** 17.5" single, 8 lug

**Tires:** (4) – 215 75 R 17.5, 16 ply radials

**Boarding Step:** Front driver side

**Storage:** tool tray w/ steel locking lid and solid bottom

**Floor:** 2" x 8" Pressure treated pine

**Breakaway kit:** 12 Volt battery, with charge wire and LED test light

**Safety chains:** (2) 3/8" w/ hook and closures

**Wiring:** run in conduit tubing with junction boxes and neatly spliced

**Lights:** LED

**Paint:** cleaned, primed and painted 100% Black (optional color)

**Warranty:** 1 year with MSO provided





## **FEATURES & HIGHLIGHTS**



*Locking tongue box w/ solid floor, Dual jacks, Adjustable 21K Demco Coupler*



*Boarding step, pockets & rub-rail, stand-up or lay flat jumbo ramps*



*Easy full-width load angle, I-Beam Frame, 102" width, 8K axles, 16 ply tires*