



25 Ton Tag-A-Long Deck-Over Equipment Trailer

Model: 8.528T25T

GVWR: 61,500 lbs. (estimated weight – 11,500 lbs.)

Load Capacity: 50,000 lbs.

Main Frame: 14" I-Beam (W14 x 30)

Inside cross members: 6" channel (C6 x 8.2)

Top cross members: pierced frame 5" channel (C5 x 6.7) (16" OC)

Braces: formed 3/16" plate braces to crossmembers

Deck Height / Width: 35" x 102"

Flatbed: 23' wood

Beavertail: 5' wood

Ramps: 8" channel, 5' x 20" wide, spring assist, OAK

Side rail: 10" channel (C10 x 15.3)

Tie Downs: (6) HD cupped style 1" D-Ring per side

Jack: (2) Dual Ram 50K dual speed

Coupler: adjustable 1" plate hitch w/ 3" pintle eye (90K)

Axles: (3) 22,500 lb. oil bath

Brakes: 12 ¼" x 7 ½" Air w/ ABS (4S/2M system)

Suspension: Hutch 9700 US tri-axle

Wheels: 17.5" dual, 8 on 275 mm

Tires: (12) – 215 75 R 17.5 H, 16 ply radials (18 ply option)

Boarding Step: Front driver side

Storage: tool tray w/ solid bottom & steel locking lid in tongue

Fenders: 1/4" checker plate over tires

Floor: OAK

Safety chains: (2) GD. 100 w/ hook and closures

Wiring: run in 1" conduit tubing with junction boxes (7-way tractor Plug)

Lights: LED (separate rear stop & turn lights)

Paint: cleaned, primed and painted 100% black (optional colors)

Warranty: 1 year with MSO provided



FEATURES & HIGHLIGHTS



HD D-RINGS & BOARDING STEP



11' AIR-ASSIST BI-FOLD RAMP OPTION



AIR-LIFT FRONT AXLE OPTION



*14" I-BEAM W/ PIERCED CROSSMEMBERS
HD FORMED CROSSMEMBER GUSSETS*



CUSTOM OPTIONS & COLORS