



8 Ton Gooseneck Deck-Over Equipment Trailer

Model: 8.530GN8T-HS

GVWR: 16,000 lbs.

Main Frame: 12" I-Beam (w/ 4" anti-twist pipe)

Inside cross members: 6" channel

Top cross members: 3" channel (16" on center)

Deck Height / Width: 34" x 102"

Flatbed: 25' wood

Beavertail: 5' self-cleaning angle cleats

Ramps: 5' x 44" wide "B&A JUMBO RAMPS™", spring assist, deck-level angle cleat

Sides: 6" channel w/ stake pockets and rub rail

Gooseneck: HD B&A 10" I-Beam

Bulkhead: 1 ½" pipe front rack

Jack: (2) Dual Ram 12K drop leg

Coupler: 2 5/16" adjustable pipe

Axles: (2) 8,000 lb. spring suspension, EZ lube with electric brake

Wheels: 17.5" single, 8 lug

Tires: (4) – 215 75 R 17.5, 16 ply radials

Spare Tire: mounted front top of GN

Boarding Step: Front driver side

Storage: steel enclosed tool tray w/ locking lid b/t gooseneck uprights

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided



FEATURES & HIGHLIGHTS



SPARE TIRE, DUAL JACKS, LOCKING TOOL BOX, BOARDING STEP, PIPE BULKHEAD



12" I-BEAM FRAME W/ 4" ANTI-TWIST PIPE, 16" ON CENTER CROSS-MEMBERS



PRESSURE TREATED PINE FLOOR



FULL WIDTH "B&A JUMBO RAMPS™"



FULL WIDTH LOADING & EASY-LOAD ANGLE



102" WIDE X 35" DECK HEIGHT