

10 Ton Gooseneck Deck-Over Hot-Shot Trailer

Model: 8.540GN10T-HS **GVWR:** 20,000 lbs.

Main Frame: 12" I-Beam w/ beam truss & 4" anti-twist pipe

Inside cross members: 6" channel Top cross members: 4" channel Deck Height / Width: 34" x 102"

Flatbed: 40' full flatbed (5' rear tail – option)

Ramps: (2) 8' rear slide-in w/ storage chute (5' x 44" wide "B&A JUMBO RAMPS™"- option)

Sides: 6" x ¼" flat w/ full-length stake pockets, chain spools, and rub rail

Tie Downs: full-length slider track w/ (10) 4" strap & binder w/ winch tightening bar

Gooseneck: 12" I-Beam

Bulkhead: 1 ½" front pipe rack **Jack**: (2) Dual Ram 12K drop leg **Coupler:** 2 5/16" adjustable pipe

Axles: (2) 10,000 lb. spring suspension, oil bath with electric brake

Wheels: 16" dual, 8 lug

Tires: (8) - 235 80 R 16 E, 10 ply radials **Spare Tire:** Mounted front top of GN **Boarding Step:** Front driver side

Storage: steel tool tray b/t gooseneck uprights w/ locking lid

Fenders: 3/16" checker plate over tires **Floor:** 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided



FEATURES & HIGHLIGHTS



FULL 40' FLATBED X 34" DECK HEIGHT



REAR SLIDE-IN RAMP STORAGE CHUTE



SPARE TIRE, DUAL JACKS, LOCKING TOOL BOX, BOARDING STEP



12" I-BEAM FRAME, TRUSS & ANTI-TWIST PIPE, PIPE TO SIDE BRACES



5' TAIL W/ 5' X 44" WIDE "B&A JUMBO RAMPS™" ***OPTION***



PRESSURE TREATED PINE FLOOR