



10 Ton Gooseneck Deck-Over Hot-Shot Trailer

Model: 8.540GN10T-HS

GVWR: 22,000 lbs. (estimated weight – 7,500 lbs.)

Load Capacity: 14,500 lbs.

Main Frame: 12" I-Beam (W12 x 16) w/ beam truss & 4" anti-twist pipe

Inside cross members: 6" channel

Top cross members: 4" channel

Deck Height / Width: 34" x 102"

Flatbed: 40' full flatbed (5' rear tail - 35' + 5' - option)

Ramps: (8' slide-in ramps w/ storage option) OR (5' x 44" wide "B&A JUMBO RAMPS™" - option)

Sides: 6" x ¼" flat w/ full-length stake pockets, chain spools, and rub rail

Gooseneck: 12" Uni-Beam

Bulkhead: 1 ½" front pipe rack

Jack: (2) Dual Ram 12K drop leg (spring loaded)

Coupler: 2 5/16" adjustable pipe

Axles: (2) 10,000 lb. spring suspension, oil bath with electric brake

Wheels: 16" dual, 8 lug

Tires: (8) - 235 80 R 16 E, 10 ply radials

Boarding Step: Front driver side

Storage: steel tool tray b/t gooseneck uprights w/ locking lid

Fenders: 3/16" checker plate over tires

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional colors)

Warranty: 1 year with MSO provided



FEATURES & HIGHLIGHTS



FULL 40' FLATBED X 34" DECK HEIGHT



REAR SLIDE-IN RAMP STORAGE CHUTE OPTION



SPARE TIRE OPTION, DUAL JACKS, LOCKING TOOL BOX, BOARDING STEP



12" I-BEAM FRAME, TRUSS & ANTI-TWIST PIPE, PIPE TO SIDE BRACES



*5' TAIL W/ 5' X 44" WIDE "B&A JUMBO RAMPSTM" ***OPTION****



PRESSURE TREATED PINE FLOOR