



12 Ton Gooseneck Deck-Over Hot-Shot Trailer

Model: 8.540GN12T-HS

GVWR: 25,900 lbs.

Main Frame & Gooseneck: 12" I-Beam w/ beam truss & 4" anti-twist pipe

Inside cross members: 6" channel

Cross members: 3" channel (pierced frame)

Deck Height / Width: 34" x 102"

Flatbed: 40' full flatbed (5' rear tail – option)

Ramps: (2) 8' rear slide-in w/ storage chute (5' x 44" wide "B&A JUMBO RAMPS™" – option)

Sides: 6" channel w/ stake pockets, chain spools, and rub rail

Tie Downs: full-length slider track w/ (10) 4" strap & binder w/ winch tightening bar

Bulkhead: 1 ½" pipe front rack

Jack: (2) Dual Ram 12K drop leg

Coupler: 2 5/16" adjustable pipe

Axles: (2) 12,000 lb. spring suspension, oil bath with electric brake

Wheels: 16" dual, 8 lug

Tires: (8) - 235 80 R 16 E, 10 ply radials (14 ply option)

Spare Tire: mounted front top of GN

Boarding Step: Front driver side

Storage: steel tool tray b/t gooseneck uprights w/ locking lid

Fenders: 3/16" checker plate over tires

Floor: 2" x 8" Pressure treated pine

Breakaway kit: 12 Volt battery, with charge wire and LED test light

Safety chains: (2) 3/8" w/ hook and closures

Wiring: run in conduit tubing with junction boxes and neatly spliced

Lights: LED

Paint: cleaned, primed and painted 100% Black (optional color)

Warranty: 1 year with MSO provided



FEATURES & HIGHLIGHTS



**12" I-BEAM FRAME – 102" WIDE
34" DECK HEIGHT**



**SPARE TIRE – DUAL JACKS - LOCKING
TOOL BOX – STEP – BULKHEAD**



**LOW-PRO PIERCED FRAME DESIGN
FULL-LENGTH RUB RAIL & STAKE POCKETS**



FULL 40' FLATBED X 34" DECK HEIGHT



SEALED WIRING & LED LIGHTS



**5' TAIL W/ 5' X 44" WIDE "B&A JUMBO
RAMPS™" ***OPTION***