



### **12 Ton Gooseneck Deck-Over Hot-Shot Trailer**

**Model:** 8.540GN12T-HS

**GVWR:** 25,900 lbs. (estimated weight – 8,250 lbs.)

**Load capacity:** 17,650 lbs.

**Main Frame:** 12" I-Beam (W12 x 19) w/ beam truss & 4" anti-twist pipe

**Inside cross members:** 6" channel

**Cross members:** 3" channel (pierced frame)

**Deck Height / Width:** 34" x 102"

**Flatbed:** 40' full flatbed (5' rear tail - 35' + 5' - option)

**Ramps:** (8' slide-in ramps w/ storage option) OR (5' x 44" wide "B&A JUMBO RAMPS™"- option)

**Sides:** 6" channel w/ stake pockets (24" on center), chain spools, and rub rail

**Gooseneck:** 12" Uni-Beam

**Bulkhead:** 1 ½" pipe front rack

**Jack:** (2) Dual Ram 12K drop leg (spring loaded)

**Coupler:** 2 5/16" adjustable pipe

**Axles:** (2) 12,000 lb. spring suspension, oil bath with electric brake

**Wheels:** 16" dual, 8 lug

**Tires:** (8) - 235 80 R 16 E, 10 ply radials

**Boarding Step:** Front driver side

**Storage:** steel tool tray b/t gooseneck uprights w/ locking lid

**Fenders:** 3/16" checker plate over tires

**Floor:** 2" x 8" Pressure treated pine

**Safety chains & brake-away:** (2) 3/8" w/ hook and closures, 12 Volt battery w/ LED test light

**Wiring & lights:** LED, w/ wiring run in conduit tubing

**Paint:** cleaned, primed and painted 100% Black (optional colors)

**Warranty:** 1 year with MSO provided



## FEATURES & HIGHLIGHTS



12" I-BEAM FRAME – 102" WIDE  
34" DECK HEIGHT



DUAL JACKS - LOCKING  
TOOL BOX – STEP – BULKHEAD



LOW-PRO PIERCED FRAME DESIGN  
FULL-LENGTH RUB RAIL & STAKE POCKETS



PRESSURE TREATED PINE FLOOR



SEALED WIRING & LED LIGHTS



FULL-WIDTH "B&A JUMBO RAMPS™"  
OPTION - SPRING ASSIST