Inspirations from Nature

Our eyes are used to admiring natural colour schemes. Which is why, for this exterior shade card we have taken inspiration from the environment around us. Nature presents us with a colour palette that is not only infinite, but colours with endless combinations. Air, water, earth and sky, and all things natural can be amazing, accessible and free sources of colour inspiration.

So, bring the great outdoors inside! Take your hue cues from Mother Nature and build decorating themes and colour schemes that are sure to please through every season.











Picture your home in different **colour** combinations before you paint it Call 1800 103 6030





Call 1800 103 6030 or SMS XP to 56767

BERGER PAINTS INDIA LIMITED

Berger House | 129 Park Street | Kolkata 700 017 Phone 91 33 22299724/28/22499754-57 www.bergerpaints.com



Exterior Collection Inspired by palettes from nature









40% Faster Painting **Dust-free Sanding** With Automatic Machines At No Extra Cost

Call 1800 103 6030 or SMS XP to 56767

To know more visit us at www.bergerpaints.com

Painting Process

SURFACE INSPECTION – Before painting the exterior walls, undertake repairs of all surface imperfections - cracks, leakages, undulations and rusting from drainage pipes.

SCRAPING – Remove all loose paint, dirt, salt deposits as well as fungus, algae and moss alternatively by wire brushing the

Berger Recommended Tool : Express Painting Sander with Paint Scraper attachment.

SURFACE CLEANING – If required apply Bio-wash to remove fungal/algae/mold growth. Apply WeatherCoat Bio-wash and leave it on for minimum 1 day. Wash the scraped surface thoroughly and allow it to dry.

Berger Recommended Tool: Express Painting Jet Washer.

CRACK BRIDGING – For filling cracks up to 5 mm use **Home** Shield Crack Fill Paste. For wider cracks, use Home Shield Advance Latex Plus, as per the product usage guidelines.

WATERPROOFING – If required apply Home Shield Latex Shield 2K on the affected areas as per the product usage guidelines.

PUTTY APPLICATION – Apply 2 coats of Bison Wall Putty with 4-6 hours of drying time. For enhanced waterproofing, application of Home Shield Waterproof Putty is recommended.

PRIMER COAT – Apply 1 coat of Seal-O-Prime, an alkali resistant primer with sealing and priming properties. Alternatively, use WeatherCoat Exterior Primer, an alkali resistant primer. Allow 4-6 hours of drying time between coats.

TOPCOAT - Apply 2 coats of Berger Exterior Emulsion as finishing coat with a drying time of 6-8 hours after each coat with recommended dilution ratio.

Berger Recommended Tools: Express Painting Airless Spray or WeatherCoat Striped Pure Acrylic Exterior Roller for undertaking topcoat application.

		Dilution Ratio* (by Volume)	Re-coating** Interval
Putty	Bison Putty	50%	4-6 Hrs
	Home Shield Waterproof Putty	50%	4-6 Hours
Primer	WeatherCoat Exterior Primer	100%	6-8 Hours
	Seal-O-Prime	100%	4 Hours
Top Coat	Walmasta/Walmasta XP Adv	60%	6-8 Hours
	WeatherCoat Smooth	40%	6-8 Hours
	WeatherCoat Anti Dustt	40%	6-8 Hours
	WeatherCoat All Guard	40%	6-8 Hours

^{*} Application by Brush, Roller, Spray.

Product Comparison Chart

	WeatherCoat All Guard	WeatherCoat Anti Dustt	WeatherCoat Smooth	Walmasta
Life	7 years	5 years	5 years	2-3 years
Coverage*	65-75 sq ft per ltr/2 coat	60-70 sq ft per ltr/2 coat	55-60 sq ft per ltr/2 coat	50-55 sq ft per ltr/2 coat
Anti-fungal Properties	Superior	Very High	High	Average
Dirt Repellent Properties	Excellent Dirt Pick-up Resistance	Best in class Dirt Pick-up Resistance	High	Average
Water Repellent Properties	Very High/ Silicon Enhanced	High	High	Average
Finish	High Sheen	Rich Sheen	Soft Sheen	Rich Matt
Warranty#	Yes	Nil	Nil	Nil
Unique Properties	Excellent Water & Dirt Repellence	Excellent Dirt Repellence	100% Acrylic Emulsion	-

*Under ideal conditions. Actual coverage may vary depending upon the method and condition of application, surface condition and emulsion bases used. #Conditions apply. For warranty details refer to warranty certificate.

XP Advanced Benefits over Regular Version

- Better finish and hiding
- ₱ 10-15% better coverage than regular emulsion
- Significantly lower smell
- Significantly improved whiteness and brightness
- ♠ Improved anti-algae and anti-fungal properties











^{**} Dilution % will vary depending on the Emulsion Bases used. Please refer product usage guidelines.

Inside

