





Cobb Technology

Part Number	Photo	Description
CTUDR-UK1.5N		Length,Thickness,Height:42.5*4.2*42 mm Voltage rating:600V(cULus), 500V(TUV) Current rating:10A(cULus), 17.5A(TUV) Solid wire:0.14-1.5M*M Stranded wire:0.14-1.5M*M
CTUDRDN-UK2.5B		Length,Thickness,Height:42.5*6.2*47 mm Voltage rating : 600V(cULus), 800V(TUV) Current rating:20A(cULus), 24A(TUV) Solid wire:0.2-4.0M*M Stranded wire:0.2-2.5M*M
CTUDR-UK3N		Length,Thickness,Height:42.5*5.2*47mm Voltage rating : 600V(cULus), 800V(TUV) Current rating:20A(cULus), 24A(TUV) Solid wire:0.2-4.0M*M Stranded wire:0.2-2.5M*M
CTUDR-UK5N		Length,Thickness,Height:42.5*5.2*47mm Voltage rating : 600V(cULus), 800V(TUV) Current rating:30A(cULus), 32A(TUV) Solid wire:0.2-6.0M*M Stranded wire:0.2-4.0M*M



Cobb Technology

CTUDR-UK6N		<p>Length,Thickness,Height:42.5*8.2*47mm Voltage rating : 600V(cULus), 800V(TUV) Current rating:50A(cULus), 41A(TUV) Solid wire:0.2-10.0M*M Stranded wire:0.2-6.0M*M</p>
CTUDR-UK10N		<p>Length,Thickness,Height:42.5*10.2*47mm Voltage rating : 600V(cULus), 800V(TUV) Current rating:65A(cULus), 76A(TUV) Solid wire:0.2-16M*M Stranded wire:0.2-10.0M*M</p>
CTUDR-UIK16N		<p>Length,Thickness,Height:42.5*12.2*47mm Voltage rating : 300V(cULus), 400V(TUV) Current rating:85A(cULus), 76A(TUV) Solid wire:2.5-25M*M Stranded wire:4-16M*M</p>
CTUDR-UK16K		<p>Length,Thickness,Height:42.5*12.2*54mm Voltage rating : 600V(cULus), 800V(TUV) Current rating:85A(cULus), 76A(TUV) Solid wire:2.5-25M*M Stranded wire:4-16M*M</p>





Cobb Technology

CTUDR-UK35N		<p>Length,Thickness,Height:50*15.2*62mm Voltage rating : 600V(cULus), 1000V(TUV) Current rating:150A(cULus), 125A(TUV) Solid wire:0.75-50M*M Stranded wire:0.75-35M*M</p>
CTUDR-UIK35N		<p>Length,Thickness,Height:55*15.2*51mm Voltage rating : 600V(cULus), 600V(TUV) Current rating:115A(cULus), 125A(TUV) Solid wire:0.75-35M*M Stranded wire:0.75-35M*M</p>
CTUDR-UKH50		<p>Length,Thickness,Height:70.5*20*83.5mm Voltage rating : 600V(cULus), 1000V(TUV) Current rating:150A(cULus), 150A(TUV) Solid wire:16-50M*M Stranded wire:25-35M*M</p>

Cobb Technology

CTUDR-UKH95		<p>Length,Thickness,Height:83*25*91.5mm Voltage rating : 726V(cULus), 1000V(TUV) Current rating:216A(cULus), 232A(TUV) Solid wire:25-95M*M Stranded wire:35-95M*M</p>
CTUDR-UKH150		<p>Length,Thickness,Height:100*31*118.5mm Voltage rating : 1100V(cULus), 1000V(TUV) Current rating:265A(cULus), 309A(TUV) Solid wire:35-150M*M Stranded wire:50-150M*M</p>
CTUDR-UKH240		<p>Length,Thickness,Height:100*31*131.5mm Voltage rating : 1100V(cULus), 1000V(TUV) Current rating:350A(cULus), 415A(TUV) Solid wire:70-240M*M Stranded wire:70-240M*M</p>
CTUDR-UK-2.5BJD		<p>Length,Thickness,Height:42.5*6.2*42mm Voltage rating : 690V Current rating:32A Solid wire:0.2-4.0M*M Stranded wire:0.2-2.5M*M</p>




Cobb Technology

CTUDR-UK-3JD		<p>Length,Thickness,Height:42.5*5.2*47mm Voltage rating : 800V Current rating:32A Solid wire:0.2-4.0M*M Stranded wire:0.2-2.5M*M</p>
CTUDR-UK-5JD		<p>Length,Thickness,Height:42.5*6.2*47mm Voltage rating : 800V Current rating:41A Solid wire:0.2-6.0M*M Stranded wire:0.2-4.0M*M</p>
CTUDR-UK-6JD		<p>Length,Thickness,Height:42.5*8.2*47mm Voltage rating : 800V Current rating:57A Solid wire:0.2-10.0M*M Stranded wire:0.2-6.0M*M</p>
CTUDR-UK-10JD		<p>Length,Thickness,Height:42.5*10.2*47mm Voltage rating : 800V Current rating:76A Solid wire:0.2-16.0M*M Stranded wire:0.2-10.0M*M</p>

Cobb Technology

CTUDR-UIK-16JD		<p>Length,Thickness,Height:42.5*12.2*47mm Voltage rating : 800V Current rating:101A Solid wire:2.5-25M*M Stranded wire:4-16.0M*M</p>
CTUDR-UK-16JD		<p>Length,Thickness,Height:42.5*12.2*54mm Voltage rating : 800V Current rating:101A Solid wire:2.5-25M*M Stranded wire:4-16.0M*M</p>
CTUDR-UK-35JD		<p>Length,Thickness,Height:50*15.2*62mm Voltage rating : 1000V Current rating:150A Solid wire:0.75-50M*M Stranded wire:0.75-35.0M*M</p>
CTUDR-UK-50JD		<p>Length,Thickness,Height:70.5*20*83.5mm Voltage rating : 1000V Current rating:150A Solid wire:0.16-50M*M Stranded wire:25-35.0M*M</p>

Cobb Technology

CTUDR-UK5-HESI		<p>Length,Thickness,Height:72.5*8.2*56.6mm Voltage rating : 600V(cULus),800v(TUV) Current rating:12A(cULus),6.3A(TUV) Solid wire:0.2-4.0M*M Stranded wire:0.2-4.0M*M</p>
CTUDR-UK5-HESILED24		<p>Length,Thickness,Height:72.5*8.2*56.6mm Voltage rating : 800v Current rating:6.3A Solid wire:0.2-4.0M*M Stranded wire:0.2-4.0M*M</p>
CTUDR-UK5-HESILED250		<p>Length,Thickness,Height:72.5*8.2*56.6mm Voltage rating : 800v Current rating:6.3A Solid wire:0.2-4.0M*M Stranded wire:0.2-4.0M*M</p>
CTUDR-UK10-DREHSI		<p>Length,Thickness,Height:62*6.2*59mm Voltage rating : 600V(cULus),800v(TUV) Current rating:10A(cULus),10A(TUV) Solid wire:0.5-16.0M*M Stranded wire:0.5-10.0M*M</p>

Cobb Technology

CTUDR-UK10-DREHSILED24		<p>Length,Thickness,Height:62*6.2*59mm Voltage rating : 800v Current rating:10A Solid wire:0.5-16.0M*M Stranded wire:0.5-10.0M*M</p>
CTUDR-UK10-DREHSILED250		<p>Length,Thickness,Height:62*6.2*59mm Voltage rating : 800v Current rating:10A Solid wire:0.5-16.0M*M Stranded wire:0.5-10.0M*M</p>
CTUDR-MBKKB2.5		<p>Length,Thickness,Height:62*5.2*47.5mm Voltage rating : 500v Current rating:24A Solid wire:0.2-4.0M*M Stranded wire:0.2-2.5M*M</p>
CTUDR-UKK3		<p>Length,Thickness,Height:62*6.2*59mm Voltage rating : 300V(cULus),500v(TUV) Current rating:20A(cULus),24A(TUV) Solid wire:0.2-4.0M*M Stranded wire:0.2-2.5M*M</p>
CTUDR-UKKB3		<p>Length,Thickness,Height:67*5.2*62mm Voltage rating : 500v Current rating:32A Solid wire:0.2-4.0M*M Stranded wire:0.2-2.5M*M</p>

Cobb Technology

CTUDR-UKK5		<p>Length,Thickness,Height:56*6.2*62mm Voltage rating : 300V(cULus),500v(TUV) Current rating:30A(cULus),32A(TUV) Solid wire:0.2-4.0M*M Stranded wire:0.2-4.0M*M</p>
CTUDR-UKKB5		<p>Length,Thickness,Height:67*6.2*62mm Voltage rating : 500v Current rating:32A Solid wire:0.2-4.0M*M Stranded wire:0.2-4.0M*M</p>
CTUDR-UK5-MTK-P/P		<p>Length,Thickness,Height:51*6.2*58.5mm Voltage rating : 600V(cULus),800v(TUV) Current rating:16A(cULus),16A(TUV) Solid wire:0.2-4.0M*M Stranded wire:0.2-4.0M*M</p>
CTUDR-URTK/S		<p>Length,Thickness,Height:51*6.2*58.5mm Voltage rating : 300V(cULus),400v(TUV) Current rating:40A(cULus),41A(TUV) Solid wire:0.5-10.0M*M Stranded wire:0.5-6.0M*M</p>

Cobb Technology

CTUDR-UDK4		Length,Thickness,Height:63.5*6.2*47mm Voltage rating : 690v Current rating:32A Solid wire:0.5-10.0M*M Stranded wire:0.5-6.0M*M
CTUDR-UK5-TWIN		Length,Thickness,Height:63.5*6.2*50.5mm Voltage rating : 300V(cULus),500v(TUV) Current rating:30A(cULus),32A(TUV) Solid wire:0.5-10.0M*M Stranded wire:0.5-6.0M*M

Notes:

1. Delivery for samples is 2 weeks
2. Standard lead time is 3-4 weeks.