

## Volta-BZ Series Low Temp Features/Options



Category	Description	Included (Base Unit)
<b>BASE Unit</b>	NEMA 4 - UL Model Low Temp -40F Unit	X
<b>ENCLOSURES</b>	NEMA 4 - UL Model Dual Cabinet (24x24x12 & 12x24x10)	X
<b>Skid Base</b>	Dual Upright with Fork Pockets	X
<b>Auxiliary Controls</b>	On/Off Power Switch	X
	E -Stop Button with Protection Shield	Consult Volta
	Adjustable Flow Restrictor( Open and/or Close)	Consult Volta
	Auxiliary Ext Hand Pump Assembly Backup	X
	Internal Heater	X
	Cold Weather Customer Tarp	Consult Volta
<b>Function</b>	Single Acting	X
	Double Acting	Consult Volta
<b>PLC</b>	Siemens LOGO	X
	Siemens TDE	X
	Modbus TCP/IP (8DI, 4RO, 2 AI)	X
<b>Main Power Battery (DC System)</b>	Optima Yellow Top D34/78	X
<b>Reservoir Size</b>	(1.4 Gallon) - Internal	X
	(3 Gallon) - External w/ Site Glass	Consult Volta
	(7 Gallon) - External w/ Site Glass	Consult Volta
<b>Power Supply</b>	24VDC	X
	120VAC / 1ph	Consult Volta
	220VAC / 1ph	Consult Volta
	480VAC / 3ph	Consult Volta
<b>Command Signal</b>	24VDC	X
	4-20mA	Consult Volta
	Modbus	Consult Volta
<b>On/Off or Modulating</b>	On/Off	X
	Modulating	Consult Volta
<i>NOTE: For modulating, we want clarification on scope to be able to price.</i>		
<b>Valve Position Indicator Integration</b>	CID1	X
	EXIA Barrier (Up to 2)	Consult Volta

## X-Standard Features