

Product Information Bulletin

LSS-5354HB

DESCRIPTION:

LSS-5354HB is a color-coded water-soluble performance product that has been designed to unload produced fluids from gas wells.

LSS-5354HB is a synergistic blend of several water-soluble components that work together to form a with a high water content.

LSS-5354HB has a high tolerance for liquid hydrocarbons and has low emulsions forming tendencies.

USAGE:

LSS-5354HB is especially effective for unloading wells that produce from 5 to 20 barrels of water per day. Most often 2 to 6 units are all that are needed to unload the well. Your Lone Star Industries Representative will work with you on designing an effective treating program.

TYPICAL PHYSICAL PROPERTIES:

Form	Solid, Cylindrical
Color	Blue
Density @ 77°F (g/ml)	1.208
Density @ 77°F (lb/gal)	10.06
pH of 1% solution	7.14

HANDLING AND STORAGE:

LSS-5354HB is an industrial chemical product. All safety and handling warnings on the product container and the material safety data sheets should be observed. For detailed safety and disposal information, please refer to the material safety data sheet. Store in a cool, dry location.

AVAILABILITY:

LSS-5354 HB is available in 5 gallon containers and split top 55 gallon drums from Lone Star Industries, 57 East Highway 359, Hebbroville, Texas 78361.

Please Call: (361)-527-4460

DISCLAIMER OF LIABILITY The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Jacam Catalyst control. The listed properties are illustrative only, and not product specifications. Jacam Catalyst disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.