



Product Information Bulletin

CLAY Sta-100 Clay Stabilizer

DESCRIPTION:

Clay Sta-100 Clay Stabilizer is designed to stabilize water sensitive clays during stimulation operations using aqueous fluids. This product will prevent swelling and migration problems which can impair the ability of a formation to produce hydrocarbons or to receive injection water.

Clay Sta-100 can also be used in HCL and HCL-HF acid systems.

PHYSICAL PROPERTIES:

Density (Lbs./Gal)	7.606
Specific Gravity @60°F	0.9131
Flash Point	90°F
Pour Point	0°F
pH	App. 7.0

Solubility

Fresh Water	Soluble
High TDS Brine	Soluble
Isopropanol	Soluble
Diesel Oil	Soluble
Heavy Aromatic Solvent	Soluble
Crude Oil	Insoluble

USAGE:

Clay Sta-100 can also be used in aqueous preflush fluids, packer fluids, acidizing fluids, and fracturing fluids. Typical dosage levels of Clay Sta-100 should be 5 gallons per 100BBLs of H₂O used.

CLAY Sta-100 Clay Stabilizer

HANDLING PRECAUTIONS:

For information regarding safety precautions in handling, health hazards, and exposure, please refer to the material safety data sheet for this product. In case of emergency, please call (361) 527-4460.

DISCLAIMER OF LIABILITY:

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Lone Star Industries' control. The listed properties are illustrative only, and not product specifications. Lone Star Industries disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.