



## Product Information Bulletin

### LSS-529

---

#### DESCRIPTION:

**LSS-529** is a color coded water soluble performance product that has been designed to unload produced fluids from gas wells, especially when the hydrocarbon content (condensate) is equal to or greater than the produced water content.

**LSS-529** is a synergistic blend of several water soluble components that work together to form a with a high water content.

#### USAGE:

**LSS-529** is especially effective for unloading wells that produce a considerable amount of hydrocarbons even when very little water is present. If your well produces more hydrocarbons than water then you should consider using **LSS-529** to unload your well. Using 2 to 6 units will do the job. Your **Lone Star Industries Representative** will work with you on designing an effective treating program.

#### TYPICAL PHYSICAL PROPERTIES:

Form	Solid, Cylindrical
Color	Tan
Density @ 77°F (g/ml)	1.198
Density @ 77°F (lb/gal)	9.58
pH of 1% solution	7.68

HANDLING AND STORAGE:

**LSS-529** is an industrial chemical product. All safety and handling warnings on the product container and the material safety data sheets should be observed. For detailed safety and disposal information please refer to the material safety data sheet. Store in a cool, dry location.

AVAILABILITY:

**LSS-529** is available in 5 gallon containers and split top 55 gallon drums from **Lone Star Industries**, P.O. Box 188, Hebronville, Texas 78361.

Please Call: (361) 527-4460

Fax: (361) 527-3089