



## Product Information Bulletin

# LSS-536

---

### DESCRIPTION:

**LSS-536** is a color coded water soluble performance product that has been designed to unload produced fluids from gas wells.

**LSS-536** is a synergistic blend of several water soluble components that work together to form a foam with a high water content.

**LSS-536** has a moderate tolerance for liquid hydrocarbons and has low emulsion forming tendencies.

### USAGE:

**LSS-536** is especially effective for unloading wells that produce from 5 to 20 barrels of water per day. Most often 2 to 6 units are all that are needed to unload the well. You **Lone Star Industries Representative** will work with you on designing and effective treating program.

Form	Solid, Cylindrical
Color	Orange
Density @ 77°F (g/ml)	1.208
Density @ 77°F (lb/gal)	10.06
pH of 1% solution	7.14

HANDLING AND STORAGE:

**LSS-536** is an industrial chemical product. All safety and handling warnings on the product container and the material safety data sheet should be observed. For detailed safety and disposal information please refer to the material safety data sheet. Store in a cool, dry location.

AVAILABILITY:

**LSS-536** is available in 5 gallon containers and 55 gallon split top drums from **Lone Star Industries**, P.O. Box 188, Hebronville, Texas, 78361.

Please Call: (361) 527-4460

Fax: (361) 527-3089