



Product Information Bulletin

OSCI-100

DESCRIPTION:

OSCI-100 is an oxygen Scavenger and Corrosion Inhibitor used for H₂O disposals. OSCI-100 should be injected into your disposal system at the point which water is discharged into the system. This will assure that the dissolved oxygen had been removed and the corrosion inhibitor will coat all metal surfaces. OSCI-100 should be injected at the rate of 50ppm (2 gallons per 1000 BBL fluid)

PHYSICAL PROPERTIES:

APPEARANCE:	Liquid, Water-White
ODOR:	Pungent Sulfur Dioxide Odor
ODOR THRESHOLD:	Not Available
pH (Neutrality):	5.0
FLASH POINT (TEST METHOD):	52°
FLAMMABILITY CLASSIFICATION:	Class I B
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	2.0 (Lowest Component)
SPECIFIC GRAVITY (Water=1):	1.156
POUNDS/GALLON:	9.629
WATER SOLUBILITY:	Complete

SHIPPING AND HANDLING:

OSCI-100 is available in 5 gallon buckets, 55 gallon drums or tote tanks.

HANDLING PRECAUTIONS:

For information regarding safety precautions in handling, health hazards, and exposure, please refer to the material safety data sheet for this product. In case of emergency, please call (361) 527-4460.

DISCLAIMER OF LIABILITY:

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Lone Star Industries control. The listed properties are illustrative only, and not product specifications. Lone Star Industries disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.

