



Product Information Bulletin

PF-200 PACKER FLUID

DESCRIPTION:

PF-200 is designed to inhibit Tubulars against corrosion due to CO² and/or H₂S. **PF-200** is stable in high temperatures. **PF-200** is completely soluble in all Brines including those found in Oilfields as well as Saturated Salt Water, Sea Waters, and Calcium Chloride Brines.

PHYSICAL PROPERTIES:

Density (Lbs./Gal)	7.477
Specific Gravity (Water = 1)	0.898
Flash Point	>200°F
Pour Point	35°F
pH	7.000

Solubility

Fresh Water	Soluble
High TDS Brine	Soluble
Crude Oil	Insoluble

USAGE:

PF-200 should be used at the rate of one Drum per 130BBLs of fluid used.

HANDLING PRECAUTIONS:

For information regarding safety precautions in handling, health hazards, and exposure, please refer to the material safety data sheet for this product. In case of emergency, please call (361) 527-4460.

DISCLAIMER OF LIABILITY The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Lone Star Industries' control. The listed properties are illustrative only, and not product specifications. Lone Star Industries disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.