

Product Information Bulletin

SC-106 Scale Corrosion Inhibitor

DESCRIPTION:

SC-106 is a high-calcium tolerant phosphonate scale inhibitor mixed with a Corrosion Inhibitor. Generally, phosphonate scale inhibitors will tend to form Calcium Phosphate when injected into produced waters containing more than about 6000 mg./L. of Calcium. However, SC-106 has been observed to tolerate up to 45,000 mg./L. of Calcium without precipitating out of solution. Primarily intended for Calcium Carbonate inhibition, SC-106 also shows activity inhibiting Calcium Sulfate scale, and some performance inhibiting Barium Sulfate.

PHYSICAL PROPERTIES:

Density (Lbs./Gal)	8.213
Specific Gravity (Water = 1)	0.986
Flash Point	>200°F
Pour Point	-20°F
pH	App. 7.0
Ionic Charge	Anionic
Solubility Fresh Water High TDS Brine Isopropanol Diesel Oil Heavy Aromatic Solvent	Soluble Soluble Dispersible Insoluble Insoluble

HANDLING PRECAUTIONS:

For information regarding safety precautions in handling, health hazards, and exposure, please refer to the material safety data sheet for this product. In case of emergency, please call (361) 527-4460.

DISCLAIMER OF LIABILITY:

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Lone Star Industries' control. The listed properties are illustrative only, and not product specifications. Lone Star Industries disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.