



Product Information Bulletin

SR-542

DESCRIPTION:

SR-542 is an aqueous solution of an alkyl amine along with other proprietary ingredients which is used to prevent precipitation of sodium chloride crystals from high chloride brines.

SR-542 may be applied over the wide range of temperatures and pressures which are typically found in producing oil and gas wells with little to no impact on performance. It accomplishes this by poisoning the nascent crystal, thereby impeding further crystal growth and precipitation from solution. This mechanism allows for higher dissolved salt content in the water phase, which promotes resolubilization of existing salt deposits. This, in turn, eliminates salt buildup on down hole tubular goods, as well as surface equipment, such as meter runs, chokes, etc.

SR-542 may be used in conjunction with products such as scale inhibitors, foamers, and is generally compatible with other anionic products.

USAGE:

SR-542 is for producing gas wells; continuous usage of SR-542 based on the produced water volume greatly reduces or eliminates the frequency of salting in the well.

Advantages:

- Inhibits salt deposition
- Dissolves high concentrations of salt
- Effective in brine
- Compatible with dispersant treatments, scale inhibitors, etc.
- Effective with anionic foamers
- Convenient solid

TYPICAL PHYSICAL PROPERTIES:

Form	Solid, Cylindrical
Color	White
Density @ 77°F (g/ml)	1.147
Density @ 77°F (lb/gal)	9.55
pH of 1% solution	7.67

HANDLING AND STORAGE:

SR-542 is an industrial chemical product. All safety and handling warnings on this product container and the material safety data sheet should be observed. For detailed safety and disposal information please refer to the material safety data sheet. Store in a cool, dry location.

AVAILABILITY:

SR-542 is available in 5 gallon containers and split top 55 gallon drums from **Lone Star Industries**, P.O. Box 188, Hebbbronville, Texas 78361.

Please Call: (361) 527-4460

Fax: (361) 527-3089

Disclaimer of Liability: The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond LSI's control. The listed properties are illustrative only, and not product specifications. LSI disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason the use of any of its products in combination with other material or in any process.