





## J TYPE SPEED NUTS











				ħ
1			$^{\prime}$	
	24		•	
			P	
_		ш		_0

	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	V. America (	
Part Number	Description	Panel Range	A B
00110/17/4/5	3/16" BSW 'J' Nut	0.70 - 1.20	19.68 12.70
00110/17/4/5	No.10 AB SMS 'J' Nut	0.70 - 1.20	19.68 12.70
00116/17/320/5	No.8 AB SMS 'J' Nut	0.70 - 1.20	16.65 11.12
01671/17/4	No.14 AB SMS 'J' Nut	0.90 - 1.60	24.65 14.50
09695/17/4	1/4" BSW 'J' Nut	0.90 - 1.90	20.32 12.70
11402/17/4	No.8 AB SMS 'J' Nut	0.70 - 1.50	13.90 / 12.70
R228/17/7R	5/16" UNC 'I' Nut	0.90 - 1.60	27 43 22 35

These highly effective spring steel 'J' Nuts are light weight, easily installed, low cost fasteners. They are used to provide strong thread forms for thin sheets which would otherwise be incapable of accepting a thread. Manufactured to suit a range of sheet thickness in one clip means that one part could be used for several different applications. The design is such, that once engaged and tightened, the clip creates a spring locking action upon the screw, therefore resisting vibration and shock loads, one reason why these clips are widely used in the domestic appliance manufacturing industries.







Unit 7/2-6 Lindsay Street Rockdale NSW 2216 www.rageem.com.au

Phone: 61 2 9599 3132 Fax: 61 2 9597 2673

Email: sales@rageem.com.au