# **Clear Sight Clearer Insight**

# **HD IP CAMERA SERIES** IPM225-7511-IM

# 5MP Compact Fisheye IP Camera FOR INTERIOR/EXTERIOR APPLICATIONS

- 5M 360° or 180° viewing angle
- · Immervision Enabled Lens
- · H.265, H.264 and MJPEG compression
- · SMART Bitrate Control and Region of Interest
- · Power over Ethernet (IEEE 802.3af)

# **CAMERA**

B5SST)
licker
0)
er)

# **IR ILLUMINATOR**

IRLED IR Working Distance

### VIDEO

Video Compression	H.265, H.264, MJPEG
Profile	H.264 : MP / HP. And H.265 : MP
Multiple Profile Streaming Performance	2592x1944/30 + 480p30 with H.264, H265 + MJPEG
Max Resolution	2592 x 1944
Video Bit Rate	100Kbps ~ 10Mbps
	Multi-rate for Preview and Recording
Bitrate Control	Multi Streaming CBR/VBR
	(Controllable frame rate and Bandwidth)
Digital Noise Reduction	3D-DNR
Privacy Mask	16 programmable zones
Special Features	SMART Bitrate Control, Region of Interest
Other Image Processing	Configurable Exposure, White Balance, Sharpness
Analogue Output-	

# 



AUDIO	
Audio Compression	G.711
Audio input / output	1/1

## **EVENT**

Event Trigger	Motion Alarm, Temperature critical, DI
Pre-Post Recording	Pre: 1~5 sec Post: 1~240 sec
Event Notification	FTP, E-mail, SD card

NETWORK		
Ethernet Standard	10 / 100 Base-T IPv4	
Protocol	TCP/IP, UDP, AutoIP, RTP(UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3(MIB-2), ONVIF	
Security	HTTPS(SSL), IP filtering, 802.1x, Digest Authentication	
Plug In	ONVIF Profile S, CGI API	

GENERAL	
Material	Aluminum Die-casting & PC, White
External I/O Terminals	
Language on webpage	English
Power Source	DC12V, PoE(IEEE 802.3af)
Power Consumption	DC12V Max 6.3W, PoE Max 7.2W
Operating Conditions	Humidity 10 ~ 90% RH (non-condensing)
	[DC12V / PoE] -20°C ~ 50°C (-4°F ~ 122°F)
Approvals	FCC, CE, IP66
Weight	0.5kg
Dimensions (W x H)	Ø125mm x 48.6mm

# **EDGE STORAGE**

Storage

1x microSD/microSDHC / microSDXC (card not included)

# Jegan

# You're Not Safe Unless You're Jogan Safe

# www.jogansecurity.com

# **Clear Sight Clearer Insight**

# **HD IP CAMERA SERIES** IPM225-7511-IM

# 5MP Compact Fisheye IP Camera

FOR INTERIOR/EXTERIOR APPLICATIONS

- 5M 360° or 180° viewing angle
- Immervision Enabled Lens
- · H.265, H.264 and MJPEG compression
- SMART Bitrate Control and Region of Interest
- Power over Ethernet (IEEE 802.3af)



## **Basic Features**

**Analytics Engine** VCA Technology's advanced tracking algorithm with rich library of detection behaviors.

**Detection Zones and Rules** 40 zones (Multi-segment Polygons and Lines) in total, 60 rules in total as standard.

**Intrusion Detection** Detection of the presence of an object.

**Tamper Detection** Supported as standard.

# **Optional Features**

**Detection Behavior** Enter, Exit, Appear, Disappear, Stop, Direction, Dwell filter, Speed filter\*1, Abandoned/Removed object filter, Tailgating, Color Filter\*1

**Logical Rules** Extends standard rules to allow various combinations of the inputs.

**3D Behavior** Perspective Corrected Size and Speed Filters.

**Object Classification** Configured Max./Min. object sizes and Max./Min.speeds.

People Tracking\*1 Tracks individuals separately among overlapped multiple people.

Counting Line High accuracy people and vehicle counting, 20 counters in total.

Meta Data JSON format, Plain XML format.

**Jada U** 

\*1: Please check the availability with your account manager.

# 

# **Basic Features**







Intrusion Detection

Tamper Detection

Camera Shake Cancelation

# **Optional Features**



Disappear

Filter

Tailgating

Filter

Tracker



Stopped Filter

Zones &

lines

Dwell

Filter

Enter & Exit

Speed Filter

3D Calibration

Object Counting

Filters





Abandoned Object Filter

Direction

Filter









Logical









www.jogansecurity.com

People

Colour Filter



