Clear Sight Clearer Insight

HD IP CAMERA SERIES IPM65A02-7311IR

STARVIS 2MP IR Bullet IP Camera FOR EXTERIOR APPLICATIONS

- · H.265, H.264 and MJPEG compression
- · Superior low light performance
- Remote zoom and focus lens (auto-focus)
- SMART Bitrate Control and Region of Interest
- Power over Ethernet (IEEE 802.3af)



CAMERA			
Model	IPM65A02-7311IR		
Image Sensor	SONY STARVIS EXMOR 1/2.8" 2.13M CMOS		
Effective Pixels	1920(H) x 1080(V)		
Scanning System	Progressive scanning		
AGC Control	Auto		
IRIS Type	P-IRIS		
Minimum Illumination	Color: 0.02Lux /B/W : 0 Lux (IR LED On)		
Lens	2.8 – 12.0 mm, F1.4		
Angle of View (2.8mm)	Horizontal: Approx. 96°(Wide) to 35° (Tele)		
Shutter Time	Auto / Manual: 1/30 ~ 1/32,000, Anti-Flicker,		
	Slow Shutter (1/2,1/3,1/5,1/6,1/7.5,1/10)		
Day & Night	True Day & Night (Removable IR-cut filter)		
Wide Dynamic Range	TrueWDR, 120 dB or above		
S/N Ratio	50dB		

IR ILLUMINATOR

IRLED	6 x High Power LED
IR Working Distance	40m

VIDEO H.265, H.264, MJPEG Video Compression H.264 : MP / HP. And H.265 : MP Profile Multiple Profile 1080p30 + D1(704x480 or 704x576) p30 with H.264, H.265 + MJPEG Performance 1920 x 1080 Max Resolution Video Bit Rate 100Kbps ~ 10Mbps Multi-rate for Preview and Recording Bitrate Control Multi Streaming CBR/VBR (Controllable frame rate and Bandwidth) 3D-DNR Digital Noise Reduction 16 programmable zones Privacy Mask **Special Features** SMART Bitrate Control, Region of Interest Other Image Processing Configurable Exposure, White Balance, Sharpness Flip / Mirror / Corridor Mode Image Orientation Analogue Output-1 (Installation only) CVBS 1.0V p-p (75Ω), 4:3 aspect ratio

AUDIO

Audio Streaming	Two way
Audio Compression	G.711
Audio input / output	1/1

EVENT

Event Trigger	Motion Alarm, Temperature critical, DI
Pre-Post Recording	Pre: 1~5 se Post: 1~240 sec
Event Notification	FTP, E-mail, Alarm-out, SD card

NETWORK

Ethernet Standard	10 / 100 Base-T
IP	IPv4
Protocol	TCP/IP, UDP, AutoIP, RTP(UDP/TCP), RTSP, NTP,
	HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP,
	SMTP, ICMP, SNMPv1/v2/v3(MIB-2), ONVIF
Security	HTTPS(SSL), IP filtering, 802.1x, Digest
	Authentication
Plug In	ONVIF Profile S, CGI API

GENERAL

Material	Aluminum Die-casting, White
External I/O Terminals	1 x Alarm In / 1 x Alarm Out
Language on webpage	English
Power Source	DC12V, PoE(IEEE 802.3af)
Power Consumption	DC12V Max 8.9W, PoE Max 10.3W
Operating Conditions	Humidity 10 ~ 90% RH (non-condensing)
이 가지 가슴 왜, 가 아랍지 않았	[DC12V/PoE] -40°C ~ 50°C (-40°F ~ 122°F)
Cold Start	Supported
Approvals	FCC, CE, IP67
Weight	0.9kg
Dimensions (W x H)	247.2mm x 96.7mm

EDGE STORAGE

Storage		Ī

1x microSD/microSDHC / microSDXC (card not included)

Jegañ

You're Not Safe Unless You're Jogan Safe

www.jogansecurity.com

Clear Sight Clearer Insight

HD IP CAMERA SERIES IPM65A02-7311IR

STARVIS 2MP IR Bullet IP Camera FOR EXTERIOR APPLICATIONS



- H.265, H.264 and MJPEG compression
- · Superior low light performance
- · Remote zoom and focus lens (auto-focus)
- · SMART Bitrate Control and Region of Interest
- Power over Ethernet (IEEE 802.3af)



Zones &

lines

Basic Features



Intrusion

Detection

Disappear

Filter

Tailgating



Tamper

Detection



Camera Shake Cancelation

Optional Features





Dwell



Enter & Exit Filters



Speed

Filter

3D Calibration



Filter







Logical







www.jogansecurity.com

VIDEO ANALYTICS

Basic Features

Analytics Engine VCA Technology's advanced tracking algorithm with rich library of detection behaviors.

Detection Zones and Rules 40 zones (Multi-segment Polygons and Lines) in total, 60 rules in total as standard.

Intrusion Detection Detection of the presence of an object.

Tamper Detection Supported as standard

Optional Features

Detection Behavior Enter, Exit, Appear, Disappear, Stop, Direction, Dwell filter, Speed filter*1, Abandoned/Removed object filter, Tailgating, Color Filter*1

Logical Rules Extends standard rules to allow various combinations of the inputs

3D Behavior Perspective Corrected Size and Speed Filters.

Object Classification Configured Max./Min. object sizes and Max./Min.speeds

People Tracking*1 Tracks individuals separately among overlapped multiple people

Counting Line High accuracy people and vehicle counting, 20 counters in total

Meta Data JSON format, Plain XML format

ada ju

*1: Please check the availability with your account manager.

Filter



Tracker

People

Filter

Filter







Counting





Filter







Object





