

Date of Issue: 3/16/2016 Supersedes: 1/31/2013

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION					
Product Identifier:	ACTCHEM 75 VC				
Recommended Use:	Refractory Material				
Supplier:	Artech Technologies, Inc.				
Manufacturer:	Xertech Specialties LLC				
Manufacturer Address:	1422 Hoelzer Ct., Dailey Industrial Park, Pacific, MO 63069				
General Phone:	(636) 271-0586	Fax:	(636) 271-0587		
Emergency Phone:	(636) 271-0586 7:00-15:00 CS	T Monda	ay-Friday		

## **SECTION 2 - HAZARDS IDENTIFICATION**

**GHS/US CLASSIFICATION** 



GHS-07

Signal Word: Danger

# **Hazard Statements:**

H315 Causes skin irritation

H320 Causes eye irritation

# **Precautionary Statements:**

P260 Do not breathe dust

- P264 Wash hands thoroughly after handling
- Wear eye protection, protective gloves P280

SECTION 3 – COMPOSITION/INFORMATION ON MIXTURE INGREDIENTS						
COMPONENT	CAS No.	%	GHS-US Classification			
Aluminum Oxide, Non-Fibrous	1344-28-1	40-70	Not classified			
Calcium Aluminate Cement	65997-16-2	7-13	Skin Irrit. 2, H315 Eye Irrit. 2B, H320			
Silica, Amorphous	69012-64-2	5-10	Skin Irrit. 2, H315 Eye Irrit. 2B, H320			

# ACTCHEM 75 VC

Safety Data Sheet

# **SECTION 4 – FIRST AID MEASURES**

#### DESCRIPTION OF FIRST AID MEASURES

**Inhalation:** Move person to fresh air. Call a physician if symptoms develop or persist.

**Skin Contact:** Wash off with soap and water. Seek medical attention if irritation develops and persists.

**Eye Contact:** Rinse eyes with water for several minutes. Seek medical attention if irritation develops.

**Ingestion:** Rinse mouth. Do not induce vomiting. Seek medical attention.

#### MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Skin Contact: Causes skin irritation.

Eye Contact: Causes eye irritation.

#### INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Treat symptomatically

## **SECTION 5 – FIRE-FIGHTING MEASURES**

#### EXTINGUISHING MEDIA

Suitable Extinguishing Media: Water spray, dry powder, foam

Unsuitable Extinguishing Media: None known

#### SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous Combustion Products: Not combustible. Hydraulic setting.

#### ADVICE FOR FIREFIGHTERS

**Fire Fighting Instructions:** Fire-fighters should use standard protective equipment in enclosed spaces, self-contained breathing apparatus (SCBA).

#### SECTION 6 – ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

**For Non-Emergency Personnel:** Ensure area is as well ventilated as possible before tackling spillage. Avoid contact with skin and eyes. Do not breathe dust.

**For Emergency Responders:** Do not attempt to take action without suitable protective equipment, including respiratory protection. For further information, refer to Section 8.

#### **ENVIRONMENTAL PRECAUTIONS**

**General:** Avoid release to the environment.

#### METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

**For Cleaning Up:** Sweep or shovel into suitable containers. Minimize generation of dust.

#### **REFERENCE TO OTHER SECTIONS**

General: See sections 8 and 13.

Safety Data Sheet

# SECTION 7 – HANDLING AND STORAGE

# PRECAUTIONS FOR SAFE HANDLING

Do not breathe dust or vapors. Provide good ventilation at all times. Keep out of the reach of children. Wash contaminated clothing before reuse. Always wash hands after handling the product.

#### CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Store this product in original packaging in a dry location where it can be protected from the elements.

#### SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### CONTROL PARAMETERS

COMPONENT	ACGIH TLV	OSHA PEL (TWA)
Aluminum Oxide, Non-Fibrous (1344-28-1)	1 mg/m <sup>3</sup> resp. dust	15 mg/m <sup>3</sup> total 5 mg/m <sup>3</sup> resp.
Calcium Aluminate Cement (65997-16-2)	3 mg/m <sup>3</sup> resp. 10 mg/m <sup>3</sup> inhalable	10 mg/m <sup>3</sup> total 5 mg/m <sup>3</sup> resp.
Silica, Amorphous (69012-64-2)	Withdrawn	80 mg/m <sup>3</sup> SiO <sub>2</sub>

Notes: TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

#### **EXPOSURE CONTROLS**

Appropriate Engineering Controls: Ensure adequate ventilation.

**Individual Protection Measures, Such As Personal Protective Equipment:** Wear appropriate dust mask. Wear protective gloves. Avoid contact with eyes. Wear goggles, suitable protective clothing, and closed footwear. Wash hands before eating, drinking, and/or smoking.

#### SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

#### INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid	Vapor Pressure:	Not applicable			
Appearance:	Granular mixture	Vapor Density (Air = 1):	Not applicable			
Color:	Light grey	<b>Relative Density:</b>	2.5			
Odor:	Earthy odor	Solubility:	Water: Slight			
pH:	No data available	Partition Coefficient:	No data available			
Melting Point:	>2400 °F	Auto-ignition Temp:	No data available			
Freezing Point:	Not applicable	Decomposition Temp:	No data available			
Boiling Point:	Not applicable	Viscosity:	Not applicable			
Flash Point:	Not applicable	Explosive Properties:	No data available			
Evaporation Rate:	Not applicable	<b>Oxidizing Properties:</b>	No data available			
Flammability (solid, gas): Not applicable						

# SECTION 10 – STABILITY AND REACTIVITY

**REACTIVITY:** Product is non-reactive under normal conditions of use, storage, and transport.

CHEMICAL STABILITY: Product is stable under normal conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:** No dangerous reactions known during recommended use.

CONDITIONS TO AVOID: Avoid dust formation. Avoid heating in fire.

**INCOMPATIBLE MATERIALS:** None detailed.

HAZARDOUS DECOMPOSITION PRODUCTS: No additional information available.

# SECTION 11 – TOXICOLOGICAL INFORMATION

#### INFORMATION ON TOXICOLOGICAL EFFECTS

Carcinogenicity:

Amorphous Silica: IARC Group 3 – not classifiable as to its carcinogenicity to humans (ACGIH).

#### Acute Toxicity:

<u>Amorphous Silica</u>: ORAL acute (LD50): 3,160 mg/kg (rat). INTRAVENOUS acute (LD50): 15 mg/kg (Rat). (RTECS) (2009). Registry of Toxic Effects of Chemical Substances, NIOSH, CDC

#### Toxicity:

Aluminum Oxide: ORAL (LD50): >10,000 mg/kg (rat)

Amorphous Silica: Tuberculosis

SECTION 12 – ECOLOGICAL INFORMATION

**ECOTOXICITY:** This product is not considered harmful to aquatic organisms or to cause long-term adverse effect in the environment.

**PERSISTENCE AND DEGRADABILITY:** No additional information available

BIOACCUMULATIVE POTENTIAL: No data available

**MOBILITY IN SOIL:** No data available

**OTHER ADVERSE EFFECTS:** No adverse effects are expected

#### SECTION 13 – DISPOSAL CONSIDERATIONS

#### WASTE TREATMENT METHODS

Waste Disposal Recommendations: Dispose in a safe manner in accordance with local regulations.

**Ecology – Waste Materials:** Avoid release to the environment.

#### **SECTION 14 – TRANSPORT INFORMATION**

In accordance with DOT, not regulated for transport

This product is not regulated for transport according to ADR/RID/ADN, IMDG, ICAO-TI/IATA-DGR

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

# ACTCHEM 75 VC

Safety Data Sheet

# SECTION 15 – REGULATORY INFORMATION

#### INTERNATIONAL REGULATIONS

**Cristobalite (14464-46-1):** IARC Group 3 (International Agency for Research on Cancer)

#### Canadian WHMIS Classification: D2B

# SECTION 16 – OTHER INFORMATION

#### ABBREVIATIONS

ACGIH: American Conference of Governmental Industrial Hygienists

DOT: Department of Transportation

IARC: International Agency for Research on Cancer

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

STOT RE 1: Specific Target Organ Toxicity, Repeated Exposure

WHMIS: Workplace Hazardous Materials Information System (Canada)

**DISCLAIMER:** Reasonable care has been taken in the preparations of the information provided, and it is believed to be accurate as of the preparation date. However, Artech Technologies LLC and/or Xertech Specialties LLC make no representation or warranties, and assumes no responsibility as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purpose prior to use. Artech Technologies LLC and/or Xertech Specialties LLC assume no liability to any user thereof, nor shall this establish a legally valid contractual relationship to the product.