## Cognac

## Cabinet Specifications

Face Frames

Face Frames are  $\frac{3}{4}$ " \* 1  $\frac{1}{2}$ " solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and bottoms.

Tops & Bottoms

Tops and bottom panels are  $\frac{1}{2}$ " thick multi-ply hardwood plywood . Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are  $\frac{3}{8}$  thick.

Toe kicks shall be 1/2" thick hardwood plywood.

4 End Panels

End panels are ½"thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed  $\frac{3}{16}$ . (5) Adjustable Shelves

Adjustable shelves are 5/8" thick multi-ply hardwood Plywood. Edge banded with wood tapes. (Exceeds industry standards.)

6 Back Panels

3+9 mm thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)

(7) Shelf Clips

Shelf clips are 6mm bore with a fluted plastic 3/8" long stem and shelf lock mechanism. Shelved are adjustable on  $2\frac{1}{2}$  increments.

3/4" Solid Hardwood door styles with straight top veneer raised panels.

Hinges

(9) Full Overlay , Concealed, 110 degree opening.

 $\frac{1}{2}$  plywood front, back and 2 sides with  $\frac{3}{8}$  drawer bottoms, screwed construction. (Exceeds industry standards.)

Drawer Glides

Side mount, epoxy coated, 3/4" extension . .(Exceeds industry standards.)

Base Corner Brackets

High impact, injection molded plastic.

Hanging Strips

Hanging strip are 3/4" \*11/4" hardwood.



