



VITOUR[®]

PERFORMANCE TIRES

TRUCK & BUS RADIAL TIRES



Product and System Certification



TS16949



ISO9001



3C



GCC



SMARTWAY




CERTIFICATIONS
IN EUROPE



CERTIFICATIONS IN EUROPE

VA01


PREMIUM REGIONAL SERVICE
ALL POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
9.00R20	16	144/142	K	19	7.00	10.20	40.12	6173	5842	130
10.00R20	18	149/146	K	19	7.50	10.95	41.50	7165	6614	135
11.00R20	18	152/149	K	20	8.00	11.54	42.72	7826	7165	135
12.00R20	20	154/151	K	21	8.50	12.40	44.29	8267	7606	120
12.00R24	20	160/157	K	20	8.50	12.40	48.27	9921	9094	130
11R22.5	16	146/143	L	20	8.25	10.98	41.50	6610	6005	120
11R24.5	16	149/146	L	20	8.25	10.98	43.46	7165	6610	120
12R22.5	18	152/149	K	22	9.00	11.81	42.72	7825	7165	135
315/80R22.5	20	157/154	K	21	9.00	12.28	42.36	9094	8267	130

VA02


PREMIUM REGIONAL SERVICE
ALL POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
215/75R17.5	16	128/126	M	16	6.00	8.31	30.20	3968	3748	109
215/75R17.5	16	135/133	J	16	6.00	8.31	30.20	4805	4540	123
235/75R17.5	16	132/129	M	16	6.75	9.17	31.38	4409	4089	120
225/70R19.5	14	128/126	L	18	6.75	8.90	31.93	3968	3748	110
245/70R19.5	14	133/131	L	18	7.50	9.76	33.03	4540	4295	110
265/70R19.5	16	140/138	L	18	7.50	10.31	34.13	5510	5200	112
285/70R19.5	16	146/144	L	18	8.25	11.14	35.24	6614	6173	130
9R22.5	14	136/134	L	18	6.75	9.02	38.35	4938	4674	120
10R22.5	16	144/142	L	18	7.50	10.00	40.16	6170	5840	130

VD68


PREMIUM ON AND OFF HIGHWAY SERVICE
DRIVE POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
225/70R19.5	14	128/126	M	19	6.75	8.90	32.17	3968	3748	102
245/70R19.5	16	136/134	L	19	7.50	9.76	33.03	4935	4670	119
265/70R19.5	16	140/138	M	20	7.50	10.31	34.13	5512	5203	112
275/70R22.5	16	148/145	M	23	8.25	10.87	37.72	6940	6390	130
285/70R19.5	16	146/144	M	21	8.25	11.14	35.24	6614	6173	130

VS68

PREMIUM HIGHWAY SERVICE
STEER POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load(lbs) Single	Max. Load(lbs) Dual	Max. Pressure (psi)
11R22.5	14	144/142	M	19	8.25	11.00	41.50	6170	5840	105
11R22.5	16	146/143	M	19	8.25	10.98	41.50	6610	6005	120
11R24.5	14	146/143	M	19	8.25	11.00	41.46	6610	6005	105
11R24.5	16	149/146	M	19	8.25	10.98	41.46	7165	6610	120
295/75R22.5	14	144/141	M	19	9.00	11.73	39.92	6170	5675	110
295/75R22.5	16	146/143	M	19	9.00	11.73	39.92	6610	6005	120
285/75R24.5	14	144/141	M	19	8.25	11.14	41.34	6170	5675	110
285/75R24.5	16	147/144	M	19	8.25	11.14	41.34	6775	6170	120

VT96


PREMIUM HIGHWAY SERVICE
ALL POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load(lbs) Single	Max. Load(lbs) Dual	Max. Pressure (psi)
11R22.5	16	146/143	M	20	8.25	11.00	41.50	6610	6005	120
11R24.5	16	149/146	M	19	8.25	11.00	43.46	7050	6610	120
12R22.5	18	152/149	M	19	9.00	11.81	42.72	7825	7165	135
255/70R22.5	16	140/137	M	16	7.50	10.04	32.68	5510	5070	120
275/70R22.5	16	148/145	M	18	8.25	10.87	37.72	6940	6390	130
285/75R24.5	14	144/141	M	19	8.25	11.14	41.34	6170	5675	110
285/75R24.5	16	147/144	M	19	8.25	11.14	41.34	6775	6170	120
295/75R22.5	14	144/141	M	19	9.00	11.73	40.16	6170	5675	110
295/75R22.5	16	146/143	M	19	9.00	11.73	40.16	6610	6005	120
295/80R22.5	18	152/149	M	19	9.00	11.73	41.10	7825	7165	130
315/80R22.5	20	157/154	M	19	9.00	12.28	42.36	9090	8265	130

VD98


PREMIUM HIGHWAY SERVICE
DRIVE POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load(lbs) Single	Max. Load(lbs) Dual	Max. Pressure (psi)
11R22.5	16	146/143	L	29	8.25	3.11	41.93	6610	6005	105
295/75R22.5	14	144/141	L	29	9.00	11.73	40.16	6170	5675	110
295/75R22.5	16	146/143	L	29	9.00	11.73	40.16	6610	6005	120
11R24.5	16	149/146	L	29	8.25	11.00	43.94	7050	6610	120
285/75R24.5	14	144/141	L	29	8.25	11.14	41.57	6170	5675	110
285/75R24.5	16	147/144	L	29	8.25	11.14	41.57	6775	6170	120

VD30

PREMIUM ON AND OFF HIGHWAY SERVICE
DRIVE POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
11R22.5	16	146/143	M	29	8.25	10.98	41.93	6610	6005	120
11R24.5	16	149/146	M	29	8.25	10.98	43.94	7165	6610	120

VT96+


PREMIUM HIGHWAY SERVICE
TRAILER POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
11R22.5	14	144/142	M	13	8.25	10.98	42.00	6170	5840	105
11R22.5	16	146/143	M	13	8.25	10.98	42.00	6610	6005	120
295/75R22.5	14	144/141	M	13	9.00	11.73	39.92	6170	5675	110
295/75R22.5	16	146/143	M	13	9.00	11.73	39.92	6610	6005	120

VD08


PREMIUM ON AND OFF HIGHWAY SERVICE
DRIVE POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
11R22.5	16	148/145	L	26	8.25	10.98	41.50	6940	6390	123
12R22.5	18	152/149	L	26	9.00	11.81	42.72	7825	7165	135
11R24.5	16	149/146	L	19	8.25	11.00	43.94	7165	6610	120

VA05


PREMIUM REGIONAL SERVICE
ALL POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
385/65R22.5	20	160	L	20	11.75	15.31	42.20	9920	----	130
425/65R22.5	20	164	K	20	12.25	16.61	44.25	11020	----	120
445/65R22.5	20	169	K	19	13.00	17.48	45.28	12785	----	130

REGIONAL

VA06

PREMIUM REGIONAL SERVICE
ALL POSITION TIRE


Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load(lbs) Single	Max. Load(lbs) Dual	Max. Pressure (psi)
385/65R22.5	20	190	L	23	11.75	15.31	42.20	9920	----	130
425/65R22.5	20	165	K	23	13.00	16.61	44.25	11350	----	119
445/65R22.5	20	169	K	23	13.00	17.48	45.28	12785	----	130

REGIONAL


VA02

PREMIUM ALL STEEL ST
RADIAL TRAILER TIRE


Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load(lbs) Single	Max. Load(lbs) Dual	Max. Pressure (psi)
ST235/80R16	14	129/125	L	13	6 1/2 J	9.25	30.80	4080	3640	110
ST235/85R16	14	126/123	L	14	6 1/2 J	9.25	31.73	3745	3415	110

HIGHWAY


VD09

PREMIUM HIGHWAY SERVICE
DRIVE POSITION TIRE


Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load(lbs) Single	Max. Load(lbs) Dual	Max. Pressure (psi)
315/80R22.5	20	157/154	K	26	9.00	12.28	42.36	9090	8265	130

MIXED SERVICE

VD05

PREMIUM ON AND OFF HIGHWAY SERVICE
DRIVE POSITION TIRE


Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load(lbs) Single	Max. Load(lbs) Dual	Max. Pressure (psi)
315/80R22.5	20	157/154	K	26	9.00	12.28	42.60	9090	8265	130

VD77

PREMIUM ON / OFF ROAD SERVICE
DRIVE POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
11R22.5	16	148/145	G	29	8.25	10.98	41.93	6940	6390	123
12R22.5	18	152/149	G	29	9.00	11.81	43.15	7825	7165	135

VD78

PREMIUM WINTER
DRIVE POSITION TIRE



Size	Ply Rating	Load Index	Speed Rating	Tread Depth (32nds)	Standard Rim	Section Width (inch)	Overall Diameter (inch)	Max. Load (lbs) Single	Max. Load (lbs) Dual	Max. Pressure (psi)
11R22.5	16	148/145	M	27	8.25	10.98	41.93	6610	6005	120
11R24.5	16	149/146	M	27	8.25	11.00	43.94	7165	6610	120

WARRANTY

TERMS AND CONDITIONS OF WARRANTY

VITOUR USA hereby warrants every tire sold is free from defects in workmanship or material related conditions. Tires eligible for claims must satisfy the following conditions:

1) FREE REPLACEMENT WARRANTY

- Valid only with the Original Purchaser and their tires installed on the original vehicle.
- Valid only to the Original Purchaser for period of three (3) years from Purchase date.
- Valid only if the defective tire's remaining tread depth is within 2/32nds of the original tread depth.
- Claims must be filed with an authorized dealer with proof of purchase where the original purchase was made.
- Defective tire is not within our NOT ELIGIBLE FOR WARRANTY clause below.

2) PURCHASE REFUND WARRANTY

- Valid only with the Original Purchaser and their tires installed from the original vehicle.
- Valid only to the Original Purchaser for period of three (3) years from Purchase date.
- Claims must be filed with an authorized dealer with proof of purchase where the original purchase was made.
- Amount of credit will base on the %percentage of tread depth remaining comparing to the original tread depth of the tire.
- FET tax and sales tax will not be refunded from the original purchase. Therefore:
- The refund will then be the %percentage of the Original purchase price after subtracting the FET and sales taxes.

3) NOT ELIGIBLE FOR WARRANTY

- Tires sold outside of US continent
- Tire damages caused by Road Hazard/Accidents/Mechanical conditions/Fire/Mishandling/Abusive use/Vandalism
- Premature or Irregular wear caused by Over/Under inflation, Run flat, Defective wheels and/or Vehicle mechanical defects.
- Damages relates to mismatch of sizes on vehicle and/or uses of tire not recommended by the vehicle intended.
- Mechanical conditions such as improper mounting, wheel imbalance, faulty shocks or brakes
- Remaining tread depth is under 2/32nds (Tires with less than 2/32nd tread depth is considered to be fully worn out)

4) CASING WARRANTY

- The Vitour tire casing are warranted for at least twice in retreading. Otherwise, a casing credit will be refunded towards the purchase of a new Vitour tire.
 - 17.5 size tires - \$20.00
 - 19.0 size tires - \$20.00
 - 22.5 size tires - \$60.00
 - 24.5 size tires - \$60.00

