



IM Series Indoor Banner LED Display

Dimensions:
640mmx480mm

Pixel Pitch:
11.5mm,1.8mm,2mm,2.5mm

Applications:
Shopping malls, airport, chain store, security,
monitoring, TV studio, education applications.



Your Vision | Our Solution

IM Series

At **AURA DISPLAY**, we take pride in delivering superior LED screen solutions by integrating the latest advancements in technology. Our commitment to excellence ensures that each screen is crafted using state-of-the-art materials and innovative techniques, providing crystal-clear images, vibrant colors, and remarkable durability. By leveraging these cutting-edge technologies, we guarantee the best possible product quality—designed to meet the highest industry standards and exceed your expectations. Whether for large-scale events or retail displays, our LED screens bring your vision to life with precision and reliability.

Multiple Control & Play mode

• Sync play/Async play/USB flash disk/WIFI/Cluster cloud play/ Wireless control/Anytime and anywhere



2-Year Warranty for Complete Peace of Mind

AURA DISPLAY stands behind the quality and durability of its LED screens. That's why every product comes with a 2-year warranty, ensuring that you are covered in the unlikely event of any defects or performance issues. Our warranty includes comprehensive support and prompt service, giving you confidence that your investment is protected. We are dedicated to providing not only exceptional products but also the peace of mind that comes with knowing we've got you covered—so you can focus on your business without worry.



Slanted



Base Standing



Hanging



Wall-mounted

IM Series Technical Specifications

Model number:	AD-IM-1.5	AD-IM-1.8	AD-IM-2	AD-IM-2.5
Pixel Pitch(mm)	1.53	1.86	2	2.5
LED Configuration	SMD1212	SMD1515	SMD1515	SMD2020
Brightness	≥600cd/m ²	≥700cd/m ²	≥700cd/m ²	≥800cd/m ²
Display Size(mm)	640mmx1920mm			
Dimension (mm)	652mmx1935mmx47mm			
Weight(KG)	45KG			
Ingress Protection	IP54			
Maintenance	Front			
Max./Avg. Power consumption	600W/200W			
Working Voltage	100-240V AC50-60Hz			
Viewing Angle(H/V)	H170°V170°			
Gray Scale	16bit			
Refresh rate	≥3840Hz			
Control Mode	WiFi/4G/USB/Computer/Mobile			
Support Input	Composite ,S-Video ,Component ,VGA ,DVI ,HDMI ,SDI			
Operating Temperature	-40℃~80℃(work) , storage for -30℃~+90℃			
Operating Humidity	10%—90%RH			

IM Series Indoor Banner LED Display

Dimensions:

640mmx480mm

Pixel Pitch:

1.5mm,1.8mm,2mm,2.5mm

Applications:

Shopping malls, airport,chain store,security, monitoring, TV studio, education applications.



Sales@auradisplay.ca



www.auradisplay.ca

